

mPDF

ChangeLog

=====

mPDF 6.0
20/12/2014

=====

New features / Improvements

Support for OpenTypeLayout tables / features for complex scripts and Advances Typography.
Improved bidirectional text handling.
Improved line-breaking, including for complex scripts e.g. Lao, Thai and Khmer.
Updated page-breaking options.
Automatic language mark-up and font selection using autoScriptToLang and autoLangToFont.
Kashida for text-justification in arabic scripts.
Index collation for non-ASCII characters.
Index mark-up allowing control over layout using CSS.
{PAGENO} and {nbpg} can use any of the number types as in list-style e.g. set in <pagebreak> using pagenumstyle.
CSS support for lists.
Default stylesheet - mpdf.css - updated.

Added CSS support

- lang attribute selector e.g. :lang(fr), [lang="fr"]
- font-variant-position
- font-variant-caps
- font-variant-ligatures
- font-variant-numeric
- font-variant-alternates - Only [normal | historical-forms] supported (i.e. most are NOT supported)
- font-variant - as above, and except for: east-asian-variant-values, east-asian-width-values, ruby
- font-language-override
- font-feature-settings
- text-outline is now supported on TD/TH tags
- hebrew, khmer, cambodian, lao, and cjk-decimal recognised as values for "list-style-type" in numbered lists and page numbering.
- list-style-image and list-style-position
- transform (on only)
- text-decoration:overline
- image-rendering
- unicode-bidi (also <bdi> tag)
- vertical-align can use lengths e.g. 0.5em
- line-stacking-strategy
- line-stacking-shift

=====

mPDF 5.7.4
15/12/2014

=====

Bug Fixes & Minor Additions

- SVG images now support embedded images e.g. <image xlink:href="image.png" width="100px" height="100px" />
- SVG images now supports <tspan> element e.g. <tspan x,y,dx,dy,text-anchor >, and also <tref>
- SVG images now can use Autofont (see top of classes/svg.php file)
- SVG images now has limited support for CSS classes (see top of classes/svg.php file)
- SVG images - style inheritance improved
- SVG images - improved handling of comments and other extraneous code
- SVG images - fix to ensure opacity is reset before another element
- SVG images - font-size not resetting after a <text> element
- SVG radial gradients bug (if the focus [fx,fy] lies outside circle defined by [cx,cy] and r) cf. pservers-grad-15-b.svg
- SVG allows spaces in attribute definitions in <use> or <defs> e.g. <use x = "0" y = "0" xlink:href =

```

"#s3" />
- SVG text which contains a < sign, it will break the text - now processed as &lt; (despite the fact
that this does not conform to XML spec)
- SVG images - support automatic font selection and (minimal) use of CSS classes - cf. the defined
constants at top of svg.php file
- SVG images - text-anchor now supported as a CSS style, as well as an HTML attribute
- CSS support for :nth-child() selector improved to fully support the draft CSS3 spec -
http://www.w3.org/TR/selectors/#nth-child-pseudo
    [NB only works on table columns or rows]
- text-indent when set as "em" - incorrectly calculated if last text in line in different font size
than for block
- CSS not applying cascaded styles on <A> elements - [changed MergeCSS() type to INLINE for 'A',
LEGEND, METER and PROGRESS]
- fix for underline/strikethrough/overline so that line position(s) are based correctly on font-
size/font in nested situations
- Error: Strict warning: Only variables should be passed by reference - in PHP5.5.9
- bug accessing images from some servers (HTTP 403 Forbidden whn accessed using fopen etc.)
- Setting page format incorrectly set default twice and missed some options
- bug fixed in Overwrite() when specifying replacement as a string
- barcode C93 - updated C93 code from TCPDF because of bug - incorrect checksum character for
"153-2-4"
- Tables - bug when using colspan across columns which may have a cell width specified
    cf. http://www.mpdf1.com/forum/discussion/2221/colspan-bug
- Tables - cell height (when specified) is not resized when table is shrunk
- Tables - if table width specified, but narrower than minimum cell width, and less than page width -
table will expand to
    minimum cell width(s) as long as $keep_table_proportions = true
- Tables - if using packTableData, and borders-collapse, wider border is overwriting content of
adjacent cell
    Test case:
    <table style="border-collapse: collapse;">
    <tr><td style="border-bottom: 42px solid #0FF; "> Hallo world </td></tr>
    <tr><td style="border-top: 14px solid #0F0; "> Hallo world </td></tr>
    </table>
- Images - image height is reset proportional to original if width is set to maximum e.g. <img
width="100%" height="20mm"
- URL handling changed to work with special characters in path fragments; affects <a> links, <mg>
images and
    CSS url() e.g. background-image
    - also to ignore "../" included as a query value
- Barcodes with bottom numerals e.g. EAN-13 - incorrect numeral size when using core fonts
-----
NB Spec. for embedded SVG images:
as per http://www.w3.org/TR/2003/REC-SVG11-20030114/struct.html#ImageElement
Attributes supported:
x
y
xlink:href (required) - can be jpeg, png or gif image - not vector (SVG or WMF) image
width (required)
height (required)
preserveAspectRatio

Note: all attribute names and values are case-sensitive
width and height cannot be assigned by CSS - must be attributes
-----
=====
mPDF 5.7.3
24/8/2014
=====
Bug Fixes & Minor Additions
-----
- Tables - cellSpacing and cellPadding taking preference over CSS stylesheet
- Tables - background images in table inside HTML Footer incorrectly positioned
- Tables - cell in a nested table with a specified width, should determine width of parent table cell
    (cf. http://www.mpdf1.com/forum/discussion/1648/nested-table-bug-)
- Tables - colspan (on a row after first row) exceeds number of columns in table
- Gradients in Imported documents (mPDFI) causing error in some browsers
- Fatal error after page-break-after:always on root level block element
- Support for 'https/SSL' if file_get_contents_by_socket required (e.g. getting images with
allow_url_fopen turned off)

```

- Improved support for specified ports when getting external CSS stylesheets e.g. `www.domain.com:80`
- error accessing local .css files with dummy queries (cache-busting) e.g. `mpdfstyleA4.css?v=2.0.18.9`
- start of end tag in PRE incorrectly changed to `<`;
- error thrown when open_basedir restriction in effect (deleting temporary files)
- image which forces pagebreak incorrectly positioned at top of page
- [changes to avoid warning notices by checking if `(isset(x))` before referencing it]
- text with letter-spacing set inside table which needs to be resized (shrunk) - letter-spacing was not adjusted
- nested table incorrectly calculating width and unnecessarily wrapping text
- vertical-align:super|sub can be nested using `` elements
- inline elements can be nested e.g. `text ^{text¹³text} text`
- CSS vertical-align:0.5em (or %) now supported
- underline and strikethrough now use the parent inline block baseline/fontsize/color for child inline elements *** change in behaviour
(Adjusts line height to take account of superscript and subscript except in tables)
- nested table incorrectly calculating width and unnecessarily wrapping text
- tables - font size carrying over from one nested table to the next nested table
- tables - border set as attribute on `<TABLE>` overrides border set as CSS on `<TD>`
- tables - if table width set to 100% and one cell/column is empty with no padding/border, sizing incorrectly
(http://www.mpdf1.com/forum/discussion/1886/td-fontsize-in-nested-table-bug-#Item_5)
- `<main>` added as recognised tag
- CSS style transform supported on `` element (only)
All transform functions are supported except `matrix()` i.e. `translate()`, `translateX()`, `translateY()`, `skew()`, `skewX()`, `skewY()`, `scale()`, `scaleX()`, `scaleY()`, `rotate()`
NB When using Columns or Keep-with-table (use `kwt`), cannot use transform
- CSS background-color now supported on `` element
- `@page :first` not recognised unless `@page {}` has styles set
- left/right margins not allowed on `@page :first`

=====
mPDF 5.7.2
28/12/2013

===== Bug Fixes

- `<tfoot>` not printing at all (since v5.7)
- list-style incorrectly overriding list-style-type in cascading CSS
- page-break-after:avoid not taking into account bottom padding and margin when estimating if next line can fit on page
- images not displayed when using "https://" if images are referenced by `src="//domain.com/image"`
- +aCJK incorrectly parsed when instantiating class e.g. `new mPDF('ja+aCJK')`
- line-breaking - zero-width object at end of line (e.g. index entry) causing a space left untrimmed at end of line
- ToC since v5.7 incorrectly handling non-ascii characters, entities or tags
- cell height miscalculated when using hard-hyphenate
- border colors set with transparency not working
- transparency settings for stroke and fill interfering with one another
- 'float' inside a HTML header/footer - not clearing the float before first line of text
- error if script run across date change at midnight
- temporary file name collisions (e.g. when processing images) if numerous users
- `<watermarkimage>` position attribute not working
- `<` (less-than sign) inside a PRE element, and NOT start of a valid tag, was incorrectly removed
- file attachments not opening in Reader XI
- JPG images not recognised if not containing JFIF or Exif markers
- instance of `preg_replace` with `/e` modifier causing error in PHP 5.5
- correctly handle CSS URLs with no scheme
- Index entries causing errors when repeat entries are used within page-break-inside:avoid, rotated tables etc.
- table with fixed width column and long word in cell set to colspan across this column (adding spare width to all columns)
- incorrect hyphenation if multiple soft-hyphens on line before break
- SVG images - objects contained in `<defs>` being displayed
- SVG images - multiple, or quoted fonts e.g. `style="font-family:'lucida grande', verdana"` not recognised
- SVG images - line with `opacity=0` still visible (only in some PDF viewers/browsers)
- text in an SVG image displaying with incorrect font in some PDF viewers/browsers

- SVG images - fill:RGB(0,0,0) not recognised when uppercase
- background images using data:image\/(jpeg|gif|png);base64 format - error when reading in stylesheet

New CSS support

- added support for style="opacity:0.6;" in SVG images - previously only supported style="fill-opacity:0.6; stroke-opacity: 0.6;"
- improved PNG image handling for some cases of alpha channel transparency
- khmer, cambodian and lao recognised as list-style-type for numbered lists

SVG Images

Limited support for <use> and <defs>

=====

mPDF 5.7.1

1/09/2013

=====

1) FILES: mpdf.php

Bug fix; Dollar sign enclosed by <pre> tag causing error.

Test e.g.: <pre>Test \$1.00 Test</pre> <pre>Test \$2.00 Test</pre> <pre>Test \$3.00 Test</pre> <pre>Test \$4.00 Test</pre>

2) FILES: includes/functions.php AND mpdf.php

Changes to preg_replace with /e modifier to use preg_replace_callback

(/e deprecated from PHP 5.5)

3) FILES: classes/barcode.php

Small change to function barcode_c128() which allows ASCII 0 - 31 to be used in C128A e.g. chr(13) in: <barcode code="54321068" type="C128A" />

4) FILES: mpdf.php

Using \$use_kwt ("keep-[heading]-with-table") if <h4></h4> before table is on 2 lines and pagebreak occurs after first line

the first line is displayed at the bottom of the 2nd page.

Edited so that \$use_kwt only works if the HEADING is only one line. Else ignores (but prints correctly)

5) FILES: mpdf.php

Clearing old temporary files from _MPDF_TEMP_PATH will now ignore "hidden" files e.g. starting with a "." .htaccess, .gitignore etc.

and also leave dummy.txt alone

=====

mPDF 5.7

14/07/2013

=====

Files changed

config.php

mpdf.php

classes/tocontents.php

classes/cssmgr.php

classes/svg.php

includes/functions.php

includes/out.php

examples/formsubmit.php [Important - Security update]

Updated Example Files in /examples/

All example files

mpdfstyleA4.css

config.php

Removed:

```
$this->hyphenateTables
$this->hyphenate
$this->orphansAllowed
```

Edited:

```
"hyphens: manual" - Added to $this->defaultCSS
$this->allowedCSStags now includes '|TEXTCIRCLE|DOTTAB'
```

New:

```
$this->decimal_align = array('DP'=>'.', 'DC'=>',' , 'DM'=>"\xc2\x20", 'DA'=>"\xd9\xab", 'DD'=>'-'
');
$this->h2toc = array('H1'=>0, 'H2'=>1, 'H3'=>2);
$this->h2bookmarks = array('H1'=>0, 'H2'=>1, 'H3'=>2);
$this->CJKforceend = false; // Forces overflowing punctuation to hang outside right margin (used
with CJK script)
```

Backwards compatability

Changes in mPDF 5.7 may cause some changes to the way your documents appear. There are two main differences:

1) Hyphenation. To retain appearance compatible with earlier versions, set the CSS property "hyphens: auto" whenever

you previously used `$mpdf->hyphenate=true`;

2) Table of Contents - appearance can now be controlled with CSS styles. By default, in mPDF 5.7, no styling is applied so you will get:

- No indent (previous default of 5mm) - (\$tocindent is ignored)
- Any font, font-size set (\$tocfont or \$tocfontsize) will not work
- HyperLinks will appear with your default appearance - usually blue and underlined
- line spacing will be narrower (can use line-height or margin-top in CSS)

New features / Improvements

Layout of Table of Content ToC now controlled using CSS styles

Text alignment on decimal mark inside tables

Automatically generated bookmarks and/or ToC entries from H1 - H6 tags

Support for unit of "rem" as size e.g. font-size: 1rem;

Origin and clipping for background images and gradients controlled by CSS i.e. background-origin, background-size, background-clip

Text-outline controlled by CSS (compatible with CSS3 spec.)

Use of <dottab> enhanced by custom CSS "outdent" property

Image HTML attributes added: max-height, max-width, min-height and min-width

Spotcolor can now be defined as it is used e.g. color: spot(PANTONE 534 EC, 100%, 85, 65, 47, 9);

Lists - added support for "start" attribute in e.g. <ol start="5">

Hyphenation controlled using CSS, consistent with CSS3 spec.

Line breaking improved to avoid breaks within words where HTML tags are used e.g. H<sub>2<sub>0

Line breaking in CJK scripts improved (and ability to force hanging punctuation)

Numerals in a CJK script are kept together

RTL improved support for phrases containing numerals and \ and /

Bidi override codes supported - Right-to-Left Embedding [RLE] U+202B, Left-to-Right Embedding [LRE] U+202A,

U+202C POP DIRECTIONAL FORMATTING (PDF)

Support for <base href=""> in HTML - uses it to SetBasePath for relative URLs.

HTML tag - added support for <wbr> or <wbr /> - converted to a soft-hyphen

CSS now takes precedence over HTML attribute e.g. <table bgcolor="black" style="background-color:yellow">

Added CSS support

- max-height, max-width, min-height and min-width for images
- "hyphens: none|manual|auto" as per CSS3 spec.
- Decimal mark alignment e.g. text-align: "." center;
- "rem" accepted as a valid (font)size in CSS e.g. font-size: 1.5rem
- text-outline, text-outline-width and text-outline-color supported everywhere except in tables (blur not supported)
- background-origin, background-size, background-clip are now supported everywhere except in tables
- "visibility: hidden|visible|printonly|screenonly" for inline elements e.g.
- Colors: device-cmyk(c,m,y,k) as per CSS3 spec. For consistency, device-cmyka also supported (not CSS3 spec)

- "z-index" can be used to utilise layers in the PDF document
- Custom CSS property added: "outdent" - opposite of indent

The HTML elements <dottab> and <textcircle> can now have CSS properties applied to them.

Bug fixes

- SVG images - path including e.g. 1.234E-15 incorrectly parsed (not recognising capital E)
- Tables - if a table starts when the Y position on page is below bottom margin caused endless loop
- Float-ing DIVs - starting a float at bottom of page and it causes page break before anything output, second new page is forced
- Tables - Warning notice now given in Table footer or header if <tfoot> placed after <tbody> and table spans page
- Columns - block with border-width wider than the length of the border line, line overflows
- Columns - block with no padding containing a block with borders but no background colour, borders not printed
- Table in Columns - when background color set by surrounding block element - colour missing for height of half bottom border.
- TOCpagebreakByArray() when called by function was not adding the pagebreak
- Border around block element - dashed not showing correctly (not resetting linewidth between different edges)
- Double border in table - when background colour set in surrounding block element - shows as black line between the 2 bits of double
- Borders around DIVs - "double" border problem if not all 4 sides equally - fixed
- Borders around DIVs - solid (and double) borders overlap as in tables - now fixed so mitred joins as in browser
- [Inadvertently improves borders in Columns because of change in LineCap]
- Page numbering - \$mpdf->pagenumSuffix etc not suppressed in HTML headers/footers if number suppressed
- Page numbering - Page number total {nbpg} incorrect - e.g. showing decreasing numbers through document, when ToC present
- RTL numerals - incorrectly reversing a number followed by a comma
- Transform to uppercase/lowercase not working for chars > ASCII 128 when using core fonts
- TOCpagebreak - Not setting TOC-FOOTER
- TOCpagebreak - toc-even-header-name etc. not working
- Parsing some relative URLs incorrectly
- Textcircle - when moved to next page by "page-break-inside: avoid"
- Bookmarks will now work if jump more than one level e.g. 0,2,1 Inserts a new blank entry at level 1
- Paths to img or stylesheets - incorrectly reading "//www.domain.com" i.e. when starting with two /
- data:image as background url() - incorrectly adjusting path on server if MPDF_PATH not specified (included in release mPDF 5.6.1)
- Image problem if spaces or commas in path using http:// URL (included in release mPDF 5.6.1)
- Image URL parsing rewritten to handle both urlencoded URLs and not urlencoded (included in release mPDF 5.6.1)
- <dottab> fixed to allow color, font-size and font-family to be correctly used, avoid dots being moved to new page, and to work in RTL
- Table {colsum} summed figures in table header
- list-style-type (custom) colour not working
- <tocpagebreak> toc-preHTML and toc-postHTML can now contain quotes

=====
mPDF 5.6
20/01/2013
=====

Files changed

mpdf.php
config.php
includes/functions.php
classes/meter.php
classes/directw.php

config.php changes

\$this->allowedCSStags - added HTML5 tags + textcircle AND

\$this->outerblocktags - added HTML5 tags
\$this->defaultCSS - added default CSS properties

New features / Improvements

CSS support added for min-height, min-width, max-height and max-width in

Images embedded in CSS

 improved to make it more robust, and
background: url(data:image... now added to work

HTML5 tags supported

- as generic block elements:
<article><aside><details><figure><figcaption><footer><header><hgroup><nav><section><summary>
- as in-line elements: <mark><time><meter><progress>
- <mark> has a default CSS set in config.php to yellow highlight
- <meter> and <progress> support attributes as for HTML5
- custom appearances for <meter> and <progress> can be made by editing classes/meter.php file
- <meter> and <progress> suppress text inside the tags

Textcircle/Circular

font: "auto" added: automatically sizes text to fill semicircle (if both set) or full circle (if only one set)

NB for this AND ALL CSS on <textcircle>: does not inherit CSS styles

attribute: divider="[characters including HTML entities]" added

<textcircle r="30mm" top-text="Text Circular Text Circular" bottom-text="Text Circular Text Circular"
divider=" • " style="font-size: auto" />

» ’ ‚ „ are now included in "orphan"-management at the end of lines

Improved CJK line wrapping (if CJK character at end of line, breaks there rather than previous wordspace)

NB mPDF 5.5 added support for <fieldset> and <legend> (omitted from ChangeLog)

Bug fixes

-
- embedded fonts: Panose string incorrectly output as decimals - changed to hexadecimal
Only a problem in limited circumstances.
*****Need to delete all ttfontdata/ files in order for fix to have effect.
 - <textCircle> background white even when set to none/transparent
 - border="0" causing mPDF to add border to table CELLS as well as table
 - iteration counter in THEAD crashed in some circumstances
 - CSS color now supports spaces in the rgb() format e.g. border: 1px solid rgb(170, 170, 170);
 - CJK not working in table following changes made in v5.4
 - images fixed to work with Google Chart API (now mPDF does not urldecode the query part of the src)
 - CSS <style> within HTML page crashed if CSS is too large (? > 32Kb)
 - SVG image nested in HTML failed to show if code too large (? > 32Kb)
 - cyrillic character p р at end of table cell caused cell height to be incorrectly calculated

=====
mPDF 5.5
02/03/2012
=====

Files changed

mpdf.php
classes/ttfontsunif.php
classes/svg.php
classes/tocontents.php
config.php
config_fonts.php
utils/font_collections.php
utils/font_coverage.php
utils/font_dump.php

Files added

```

-----
classes/ttfontsuni_analysis.php

config.php changes
-----
To avoid just the border/background-color of the (empty) end of a block being moved on to next page
(</div></div>)
$this->margBuffer = 0;           // Allow an (empty) end of block to extend beyond the bottom margin
by this amount (mm)

config_fonts.php changes
-----
Added to (arabic) fonts to allow "use non-mapped Arabic Glyphs" e.g. for Pashto
'unAGlyphs' => true,

Arabic text
-----
Arabic text (RTL) rewritten with improved support for Pashto/Sindhi/Urdu/Kurdish
Presentation forms added:
    U+0649, U+0681, U+0682, U+0685, U+069A-U+069E, U+06A0, U+06A2, U+06A3, U+06A5, U+06AB-U+06AE,
    U+06B0-U+06B4, U+06B5-U+06B9, U+06BB, U+06BC, U+06BE, U+06BF, U+06C0, U+06CD, U+06CE, U+06D1,
    U+06D3, U+0678
Joining improved:
    U+0672, U+0675, U+0676, U+0677, U+0679-U+067D, U+067F, U+0680, U+0683, U+0684, U+0687, U+0687,
    U+0688-U+0692,
    U+0694, U+0695, U+0697, U+0699, U+068F, U+06A1, U+06A4, U+06A6, U+06A7, U+06A8, U+06AA, U+06BA,
    U+06C2-U+06CB, U+06CF

Note -
Some characters in Pashto/Sindhi/Urdu/Kurdish do not have Unicode values for the final/initial/medial
forms of the characters.
However, some fonts include these characters "un-mapped" to Unicode (including XB Zar and XB Riyaz,
which are bundled with mPDF).
'unAGlyphs' => true,
added to the config_fonts.php file for appropriate fonts will

This requires the font file to include a Format 2.0 POST table which references the glyphs as e.g.
uni067C.med or uni067C.medi:
    e.g. XB Riyaz, XB Zar, Arabic Typesetting (MS), Arial (MS)
NB If you want to know if a font file is suitable, you can open a .ttf file in a text editor and
search for "uni067C.med"
    - if it exists, it may work!
Using "unAGlyphs" forces subsetting of fonts, and will not work with SIP/SMP fonts (using characters
beyond the Unicode BMP Plane).

mPDF maps these characters to part of the Private Use Area allocated by Unicode U+F500-F7FF. This
could interfere with correct use
    if the font already utilises these codes (unlikely).

mPDF now deletes U+200C,U+200D,U+200E,U+200F zero-widthjoiner/non-joiner, LTR and RTL marks so they
will not appear
    even though some fonts contain glyphs for these characters.

Other New features / Improvements
-----
Avoid just the border/background-color of the (empty) end of a block being moved on to next page
(</div></div>)
    using configurable variable: $this->margBuffer;

The TTFontsUni class contained a long function (extractcoreinfo) which is not used routinely in mPDF
This has been moved to a new file: classes/ttfontsuni_analysis.php
The 3 utility scripts have been updated to use the new extended class:
    - utils/font_collections.php
    - utils/font_coverage.php
    - utils/font_dump.php

Bug fixes

```

- Border & background when closing 2 blocks (e.g. </div></div>) incorrectly being moved to next page because incorrectly calculating how much space required
- Fixed/Absolute-positioned elements not inheriting letter-spacing style
- Rotated cell - error if text-rotate set on a table cell, but no text content in cell
- SVG images, text-anchor not working
- Nested table - not resetting cell style (font, color etc) after nested table, if text follows immediately
- Nested table - font-size 70% set in external style sheet; if repeated nested tables, sets 70% of 70% etc etc
- SVG setting font-size as percent on successive <text> elements gives progressively smaller text
- mPDF will check if magic_quotes_runtime set ON even >= PHP 5.3 (will now cause an error message)
- not resetting after 2 nested tags of same type e.g. bold still bold
- When using charset_in other than utf-8, HTML Footers using tags e.g. <htmlpageheader> do not decode correctly
- ToC if nested > 3 levels, line spacing reduces and starts to overlap

=====

mPDF 5.4
14/02/2012

=====

Files changed

mpdf.php
config.php
compress.php
classes/ttfontsuni.php
classes/barcode.php
classes/indic.php
classes/svg.php
examples/show_code.php ----- SECURITY RISK**
examples/example49_changelog.php
examples/example57_new_mPDF_v5-3_active_forms_b (replace example57_new_mPDF_v5-3_active_forms)
includes/out.php
mpdfi/fpdfi_pdf_parser.php

Files added

classes/bmp.php
classes/directw.php
classes/form.php
classes/grad.php
classes/tocontents.php
classes/wmf.php
examples/example58_new_mPDF_v5-4_features

config.php changes

Edited: \$this->allowedCSStags, \$this->innerblocktags, \$this->defaultCSS; (CAPTION added in each case)
Moved: Numerous \$form_.. variables are now in /classes/form.php

New config variables

\$this->bookmarkStyles = array();
\$this->cacheTables = true;

New methods

function CircularText()
function SetVisibility()

New/Extended CSS

box-shadow (block elements - does NOT support "inset")
text-shadow (all text elements - does NOT support "blur")
visibility: visible|hidden|printonly|screenonly (block-level elements and images IMG only)
text-transform: capitalize|uppercase|lowercase (extended to support TD/TH)

tr|td|th:nth-child(odd|even|2n+1)
color, strikethrough, underline and background-color (extended to support rotated TD/TH)
underline and strike-through (extended to support TD/TH)
underline (line colour) (extended to work correctly in watermark)
page-break-after: left|right|always (block elements and tables)
NB respects \$mpdf->restoreBlockPagebreaks = true; i.e. will make pagebreak act like formfeed
background[-color]: extended to support rgba|cmyka|cmyk|hsla|hsl|spot
border(extended to support inline elements)

New HTML

<caption>
<textcircle />

New features / Improvements

Tables - Zebra Stripes
Tables: overlapping rowspans (partially) supported
Tables - Disk caching
Using progress bars (or \$showStats) now reports 'real' memory usage i.e. get_memory_usage(true)
Support for query string in the URLs for external stylesheets e.g. @import url("style.css?ltyy7");
Table caption partially supported
CircularText
BookMark styling
Spread tables i.e. can split table (columns) across several pages width.
Can use chelvetica, ctimes and ccourier to specify core fonts in a non-core font document
Spread tables i.e. can split table (columns) across several pages width.
{colsum} in <tfoot> cell will insert a column total per page.
SVG embedded as island in HTML supported
Active Forms
 textarea and input (text types) now accept javascript as:
 onKeystroke, onValidate, onCalculate and onFormat
 onChange is deprecated but works as onCalculate (for textarea and input)
 (PS Select still accepts onChange cf. 5.3.37)
Ledger and Tabloid added as page formats recognised. NB Ledger is same as tabloid but landscape. In
mPDF, both give the same size (portrait)
so need to add -L e.g. Ledger-L for landscape.

Internal script changes

Changed this->k to _MPDFK throughout all scripts
Changes to color (packed binary data in string rather than array) to reduce memory usage esp in tables
Internal variables Removed
 \$usetableheader;
 \$tableheadernrows;
 \$tablefooternrows;
vars \$ChangePage, \$p_bottom_border, \$img_margin_top(+) \$issetcolor + other similar removed

Removed a whole load of // comments
Updates to remove some more Warning Notices (not all marked in text)
Border set on TR - changed so set on each cell, rather than retrospectively at end of TR
All references to table['text'] removed as not needed - uses ['textbuffer'] instead
OpenTag(TD) changes to reduce memory usage with tables
Includes different method to set a default timezone
fn _smallCaps does not need (undefined) \$space
this->chrs and this->ords replaced by chr() and ord()
Headers in out.php updated to match those used in Output()
Change to SetFont() to improve performance time
Change to GetStringWidth() to improve performance time
Corrected copying of Glyphs 0,1,2, to all subset fonts (non-SMP/SIP), and only setting 32->127 in
subset
Subset fonts (non-SMP/SIP) have additionally Unicode CMap tables (0,0,4 and 0,3,4) as well as
Microsoft (3,1,4)
Subset fonts (SMP/SIP) have CMap tables (1,0,6 and 3,0,4) - rather than 1,0,6 and 3,0,6
Subset fonts (SMP/SIP) have 'name' table changed to give 1,0 and 3,0. As it is a symbol font (not
Unicode encoded) :
 needs to have a name entry in 3,0 (e.g. symbol) - original font will have 3,1 (i.e. Unicode)

Automatically checks for HTML code length > 100000 characters and gives error warning if
PHP < 5.2.0 (as not configurable) or increases pcre.backtrack_limit if PHP < 5.3.7

Removed/Depracated

```
function UseTableHeader($opt=true)  fn removed / depracated
function UsePRE($opt=true) removed
$attr['REPEAT_HEADER'] == true      CSS removed / depracated
$this->usepre=true; removed / depracated as never needed - always respects PRE whitespace
```

ToC: NB Values can no longer be set directly e.g. as in example

```
$mpdf->TOCheader = array();      // array as for setting header/footer
$mpdf->TOCfooter = array();      // array as for setting header/footer
$mpdf->TOCpreHTML = '<h2>Contents - Portrait</h2>';      // HTML text to appear before table of
contents
```

```
$mpdf->TOCpostHTML = '';      // HTML text to appear after table of contents
$mpdf->TOCbookmarkText = 'Content list';      // Text as it will appear in the Bookmarks (leave
blank for none)
```

Need to use TOCpagebreak either direct (or array version) or as HTML

OR if absolutley necessary, could use:

```
$mpdf->tocontents->TOCheader = array();      // array as for setting header/footer
$mpdf->tocontents->TOCfooter = array();      // array as for setting header/footer
$mpdf->tocontents->TOCpreHTML = '<h2>Contents - Portrait</h2>';      // HTML text to appear
before table of contents
```

```
$mpdf->tocontents->TOCpostHTML = '';      // HTML text to appear after table of contents
$mpdf->tocontents->TOCbookmarkText = 'Content list';      // Text as it will appear in the
Bookmarks (leave blank for none)
```

Further Details

=====

CSS border on inline elements

Support for CSS border (and variants) on inline elements e.g. ``

Border styles solid|dotted|dashed|double only are supported. Border radius not supported.

Nested inline elements will have repeat left|right borders on the nested content (unlike browsers)

Tables - Zebra Stripes

TABLE - striped rows cf. <http://dev.opera.com/articles/view/zebra-striping-tables-with-css3/>

```
tr:nth-child(odd) { background-color: #99ff99; }
thead tr:nth-child(3n+2) { background-color: #FFBBFF; }
td:nth-child(2n+1) { background-color: #BBBBFF; }
table.zebraTable td:nth-child(2n+1) { background-color: #BBBBFF; }
table.zebraTable th:nth-child(2n+1) { background-color: #BBBBFF; }
```

NB mPDF does NOT correctly apply specificity to all CSS

```
table.zebra tbody tr:nth-child(2n+1) td { background-color: #FFFFBB; }
table.zebra tbody td:nth-child(odd) { background-color: #BBBBFF; }
```

should make every odd row yellow, and every odd coloumn blue, but with the row/yellow overriding the column/blue.

In mPDF the `td:nth-child(odd)` trumps the plain `td`, so the column colour wins out. You can force the effect you want by using

```
table.zebra tbody tr:nth-child(2n+1) td:nth-child(1n+0) { background-color: #FFFFBB; }
```

(The `:nth-child(1n+0)` selector just selects every `td` cell.)

Tables - Disk caching

TABLES: using disk caching

// Using disk to cache table data can reduce memory usage dramatically, but at a cost of increased
// executon time and disk access (read and write)

```
$this->cacheTables = true;
```

NB `$this->packTableData` will be overridden to `=> true`; // required for `cacheTables`

```
$this->simpleTables will be overridden to => false; // Cannot co-exist with cacheTables
```

Table caption

Must come immediately after <table...>

CSS caption-side and HTML align attribute of top|bottom supported (not attribute left|right)

Handled as a separate block element brought outside the table, so:

- CSS will not cascade correctly on the table

- width of caption block is that of page or of the block element containing the table

- so alignment will be to the page-width not the table width

- if table page-break-after: always, the caption will follow the pagebreak.

This does work:

```
<style>
```

```
.tablecaption { caption-side: bottom; text-align: left; font-weight: bold; color: green; }
```

```
</style>
```

```
...
```

```
<table>
```

```
<caption class="tablecaption">Caption title here</caption>
```

```
<tbody>
```

CSS visibility: printonly, screenonly

Roughly based on CSS

Works on Block elements P, DIV etc, or Image

Cannot nest / layer.

Inner blocks/image with set visibility are ignored if already set on enclosing block element.

(Block element) does not work inside table (image does)

So 'visible' does nothing but is set as default

(NB Changes output to PDF version 1.5)

Incompatible with PDF/A / PDF/X

'visibility'

- Value: visible | hidden | (collapse | inherit)

- Initial: visible

- Applies to: all elements

- Inherited: yes

The 'visibility' property specifies whether the boxes generated by an element are rendered.

Invisible boxes still affect layout (set the 'display' property to 'none' to suppress box generation altogether).

Values have the following meanings:

visible

- The generated box is visible.

hidden

- The generated box is invisible (fully transparent, nothing is drawn), but still affects layout.

- Furthermore, descendants of the element will be visible if they have 'visibility: visible'.

collapse | inherit

- NOT supported in mPDF

CUSTOM:

printonly | screenonly

Added VISIBILITY function

\$mpdf->SetVisibility('screenonly'); or 'printonly' 'visible' or 'hidden'

(NB Changes output to PDF version 1.5)

Incompatible with PDF/A / PDF/X

CircularText

```
function CircularText($x, $y, $r, $text, $align='top', $kerning=120, $fontwidth=100) {
```

```
x: abscissa of center
```

```
y: ordinate of center
```

```
r: radius of circle
```

```
text: text to be printed
```

```
align: text alignment: top or bottom. Default value: top
```

```
kerning: spacing between letters in percentage. Default value: 120. Zero is not allowed.
```

fontwidth: width of letters in percentage. Default value: 100. Zero is not allowed

- now uses Kerning between letters if useKerning == true (set manually see example)

BookMark styling

New configurable variable to control appearance of Bookmarks e.g.

```
$this->bookmarkStyles = array(
    0 => array('color'=> array(0,64,128), 'style'=>'B'),
    1 => array('color'=> array(128,0,0), 'style'=>'),
    2 => array('color'=> array(0,128,0), 'style'=>'I'),
);
```

Column sums

(Also changed some preg_replace to str_replace to improve performance)

To use: just add {colsum} to any cells of the table footer <tfoot>

The width of the column will be calculated using the actual string {colsum} as a placeholder.

If you need the column to be wider, use underscores "_" to pad it e.g. {colsum2_____}

Spread tables

i.e. can split table (columns) across several pages width.

CSS <table style="overflow: visible">

Cannot use with:

\$this->kwt - ignored

\$this->table_rotate - ignored

\$this->table_keep_together - ignored

\$this->ColActive - cancels spread tables

Messes up with:

\$mpdf->forcePortraitHeaders = true;

\$mpdf->forcePortraitMargins = true;

Problems with CJK, and RTL

Will do no resizing of fonts at all.

Maximum width of column = page width i.e. will not split columns across pages - NB will keep colspan>1 on one page

If table row too high for page will die with error message.

Will override some specs for width if this creates conflicts

Recommended to specify absolute value of width on each column.

Bug fixes

=====

Dottab - if text after dottab is hyperlinked <a> then dots are underlined

page-break-before now respects \$mpdf->restoreBlockPagebreaks = true; i.e. will make pagebreak act like formfeed

Annotation() function called directly with colorarray(r,g,b)

Added urldecode to _getImage to cope with ../name%20of%20image.jpg

Added urldecode AND htmlspecialchars_decode to href in <a> link e.g.

<https://www.google.com/search?hl=en&q=mpdf&filename=name%20of%20file>

[barcode.php] Allow in C39 codes - will be changed to spaces

<table> inside a <div position:fixed, left:300px;> not calculating table width correctly

- leading to either upside down table or error width less than 1 character

Depracated magic_quotes_runtime() in compress.php

DIRECTW included twice in compress.php

FORMS mark up for compress.php corrected

double backslashes not preserved inside <pre> or <textarea>

font-weight and font-style not recognised in <pageheader>

Progress bars causing corrupt PDF file (out.php) changed fopen from "r" mode to "rb" (binary)
Target around image - `` - not working

SmallCaps in `<thead>` error

Fonts with "name" table in format 1 not recognised correctly

Rotated table which does not fit on remaining page, forces a new page even if already at top of page

Locale causing problems - all instances of `sprintf()` using `%.3f` changed to `%.3F` so not locale aware

CSS border radius not implemented on fixed/absolute positioned block element

Background color in rotated table extending way beyond bottom of table

Nested table containing `<thead>` or `<tfoot>` was confused with `<thead>` or `<tfoot>` of parent table

Correct handling of spaces, `<` or `&` in textarea

`<option>` and `<input ..>` attributes value/title decoded with `fn lesser_entity_decode` instead of `htmlspecialchars_decode` to include `'`;

line width not restored to correct value after "line-through" text in `Cell()`

Kannada - incorrect positioning of Reph

Forms - In `<input>` or `<option>` (select) not correctly handling HTML named entities e.g. `<` in value or title

Active forms - ` ` as Value or Title incorrectly showing as Euro - `PDFDocEncoding` fixed

Unicode data in embedded fonts not encrypted when doc encrypted

Nested block elements which are empty including innermost one, top margin of innermost block was ignored

font-size: xx% inside a block was setting on block's parent font-size

Active forms - radio buttons (removed name from Widget - leave on Radio group)
causing problems accessing field for radio buttons

When using simple tables and border-collapse, if table border set, but cell borders not set, should display table border (fixed)

position:fixed block - if neither top nor bottom nor height specified, was positioned incorrectly (y)
Leave - if top, bottom, margin-top, margin-bottom and height are all left unspecified (or auto), will centre vertically

on the page (specific to mPDF - not consistent with CSS2.1)

But if any one of them are specified (including e.g. `margin-top=0`), follows CSS spec, so top is the current "static" position

background-image-opacity=0 not working on BODY or BLOCK

Lists - if LI continues after a nested List, would add as a new LI item (should continue as part of earlier LI item)

`fn WriteCell()` converts to 'windows-1252' when required

if multiple calls to mPDF used, cannot redefine function `cmp()`

internal link targets `` in ToC not moved when using: `page-break-inside:avoid`

internal link targets `` not moved when using: `columns`, `page-break-inside:avoid`, `keep-with-table` or `table rotate`

Active Forms - `onChange` not working for SELECT (cf. 5.3.25) Example 57 only worked by chance as JS was carried over from Select to Text field

Bug is fixed, but example file needed updating to `onCalculate` for the display field.

Table cell: if height set as %, currently sets it as % of page-width; instead this now ignores it.

Bengali letter Khanda Ta (U+09CE) character not recognised; was added in Unicode v4.1 and prior to this, (U+09A4 U+09CD U+200D)

so mPDF converts to this string and seems to work.

OCR characters wrong size in barcodes if using different ocr font - fixed

=====
mPDF v5.3 (21/07/2011)
=====

New Features

- Active forms (see on-line manual for details)
- 128-bit encryption (optional) with additional user-permissions (see on-line manual)

PLEASE READ - Change in Font management

The font name imported from the font and included by mPDF in the PDF file was stripping any '-' in the name.

This is the PostScript name which is utilised by some PostScript programmes.

mPDF has been changed to leave the PostScript font name unchanged. In 99% cases no difference will be noted, but

you MUST delete all the temporary font data files cached in the /ttfontdata/ folder for this to be effective.

Minor changes

If @page CSS is used to select a first page with settings different from the default, mPDF did create a blank page

then pagebreak to the new @page settings - this has been changed so it now will start with the new page settings.

New function added: DeletePages(\$start_page, \$end_page=-1) e.g. \$mpdf->DeletePages(1);

Can be used just before calling Output()

compress.php utility extended to exclude active forms and images-svg

Bug fixes

- list-style-type: (custom version, user-defined bullet) colour change not working if colour is set on the list item line
- background-image: SVG or WMF images as background-images in tables/tr/cells not working
- font-weight: bold font not always reset after inline ... thus miscalculating width
- forms (inactive) in 'c' core fonts using unicode characters 127-255 incorrect display in input text and button text
- form elements (inactive) if in-line with mixed size fonts, error in vertical positioning of text related to box
- ToC: wrapped lines in ToC not retaining formatting e.g. bold style
- HTMLHeaders: using setAutoTopMargin="pad"; not correctly setting top margin for first page
- output headers changed: Content-length not used if server uses output compression
- embedded font subsets from fonts which contain non-BMP plane 0 characters (incl. e.g. dejavusanscondensed)
 - causing Adobe Reader to create a CJK encoded font subset internally when loading interactive Forms
 - Changed so unsets the flag in the subset font to show no non-BMP characters.

Configurable variables added (see config.php file):

All for Active Forms:

```
$this->useActiveForms  
$this->formExportType  
$this->formSubmitNoValueFields  
$this->formSelectDefaultOption  
$this->form_border_color  
$this->form_background_color  
$this->form_border_width  
$this->form_border_style  
$this->form_button_border_color  
$this->form_button_background_color  
$this->form_button_border_width  
$this->form_button_border_style  
$this->form_radio_color  
$this->form_radio_background_color
```

PLUS: see additional values added to `$this->allowedCSStags` close to bottom of file - required for Active forms

Updated files

mpdf.php
config.php (NB as well as form stuff at top, 5.2.07 `$this->allowedCSStags` close to bottom of file)
compress.php
classes/ttfontsuni.php
examples/example57...
examples/formsubmit.php

=====
mPDF v5.2 (18/06/2011)
=====

New Features

Improvements in font handling resulting in clearer display of fonts on screen, and improved compatibility with PostScript drivers
(e.g. use with GSView/GhostScript, see below)

CJK line-breaking implemented (roughly) according to rules. Configurable variables allow control of behaviour (except in tables).

Viewer preferences: added options for initial 2 page display where you can specify whether 1st page is on left or right (cf. `SetDisplayMode`).

Custom list-style-type for a list (`ul,ol`) or a list-item (`li`) in which you can determine the character and colour of the bullet:

list-style-type: U+263Argb(255,0,0); - where U+263A is the Unicode HEX value of the character you want for the bullet
- character MUST be included in the font used for that list item. `rgb()` bit is optional

Bug fixes

- Fonts: embedding a BMP TTC font (e.g. Cambria) as a full font caused error
- Table: If cell width set by CSS as %, and page-break-inside avoid requires a new page, was losing the sizing
- Table: table borders CSS parsing error; if border-width, border-style, border-color set, not inherited correctly
- Table: Table background image or gradient not working in HTMLHeader/Footer
- Table: background color set on table (anywhere) will overwrite image/gradient
- Table Background image/gradient: If left/right margin is set on table, gradient/image set on table is too wide
- Table: rotated table - height (after first page does not correctly allow for thead i.e. too much)
- Table: blank `<tr></tr>` causes error
- Table/Letter-spacing: If letter-spacing set inside table, not calculating table width correctly, and if oversized, freezes
- ToC: ToC at top of page (non-mirrored or already ODD) did not reset page_number if told
- Character substitutions: characters missed if first element in a `$html` code e.g. `WriteHTML('Not in a tag ✓');`
- Kerning: kerning info: if reading font file for first time (or if not cached in `ttfontdata/`) did not register kerning info
- Textarea: multiple new lines run into only one newline
- QRcode - colors wrong because QRcode class only accepts RGB input (hardcoded now to always give black on white)
- QRcode always producing "Your message here"
- Columns: if transforming height of column, not always closing transform Q
- CakePHP compatibility
- compress.php - error due to markup comments in `mpdf.php` script file

Backwards compatibility

Changes in mPDF 5.2 are backwards compatible with version 5.1

Your document fonts may appear slightly different in the PDF viewer because of the changes to embedded

font subsets (cf.)

The new Indic fonts may result in a change in spacing (due to the different character width of the space character from the original font)

PostScript e.g. GSView/GhostScript

A number of errors have been reported when opening mPDF-created PDF files with a PostScript programme. Some of the errors were due to mPDF, but others were due to peculiarities of GSView/GhostScript.

- Diacritic Characters were not displayed when embedding a font subset
 - Fonts containing SIP/SMP characters (supplementary Unicode planes) caused errors
 - Error with text justification (word-spacing) when embedding a full font can occur in some fonts*
- The first 2 problems should now be fixed in v5.2

*The error with text justification can be optionally fixed by setting the configurable variable in config.php:

```
$this->repackageTTF = true;
```

When mPDF embeds a full font, it simply embeds the whole original TTF file into the PDF document. For some fonts (containing a GSUB table) this was causing problems. \$this->repackageTTF forces mPDF to repackage the original TTF file excluding some of the tables like GSUB.

(See ADDITIONAL INFO FONTS.txt in downloaded files)

Font appearance in PDF viewer

Font subsetting has been improved to include additional information in the embedded file. Overall the effects are of greater clarity when viewing the document on a screen (it will not affect print output), but the changes are dependent on:

- the original TTF font i.e. the options that the font's author has built into the file
- the PDF viewer i.e. whether the programme chooses to use the available information
- the resolution (zoom) of the page you are viewing

(See ADDITIONAL INFO FONTS.txt in downloaded files)

Indic fonts

A new set of Indic fonts (ind_xx_1_001) is distributed with version 5.2 containing the additional font information as described above.

In addition, some changes have been made to the ASCII characters in the font from the files previously distributed:

The original files (Raghu font files) do not contain the characters a-z and A-Z. When the first version indic files were created for mPDF,

ALL of the ASCII characters (32-127) were inserted/overwritten from DejaVuSansCondensed to make the font more usable.

In the latest version, only the missing characters are taken from DejaVuSansCondensed, leaving punctuation and numerals from the original fonts. This also means that the space character has a different width, and this will cause slight changes to the word spacing in documents.

(See ADDITIONAL INFO FONTS.txt in downloaded files)

CJK line-breaking (text wrapping)

CJK (chinese-japanese-korean) text often contains no spaces. mPDF previously has wrapped text whenever a character reached the end of

the line. mPDF version 5.2 attempts to follow the line-breaking rules described for each of the languages. Configurable variables

allow some control over this behaviour, especially whether to squeeze a character into the space available at the end of a line, or

whether to allow it to overflow the right margin.

Configurable variables (see config.php file):

Control wrapping of CJK text:

```
$this->allowCJKorphans = true; // FALSE=always wrap to next line; TRUE=squeeze or overflow  
$this->allowCJKoverflow = false; // FALSE=squeeze; TRUE=overflow (only selected)
```

When Embedding full TTF font files, remakes the font file using only core tables

May improve function with PostScript printers
\$this->repackageTTF = false;

Updated files

mpdf.php
compress.php
utils/font_dump.php
classes/ttfontsuni.php
config.php (3 new variables - see above)

All ttfonts/ind_*

New set of Indic fonts for PostScript compatibility - and clearer font display

=====
mPDF v5.1 (27/02/2011)
=====

New Features

- CSS background (images, colours or gradients) on <TR> and <TABLE>
- CSS border on <TR> (only in border-collapsed mode)
- support for Mozilla and CSS3 gradient syntax:
 - moz-linear-gradient, linear-gradient
 - moz-radial-gradient, radial-gradient
 - moz-repeating-linear-gradient, linear-repeating-gradient
 - moz-repeating-radial-gradient, radial-repeating-gradient
- expanded support for gradients (including in SVG images):
 - multiple colour 'stops'
 - opacity (transparency)
 - angle and/or position can be specified
- gradient can be used as an image mask (custom mPDF styles: gradient-mask)
- image-orientation supported for (similar to existing custom mPDF attribute: rotate) [CSS3]
- image-resolution supported for [CSS3]
- background-image-resolution (custom mPDF CSS-type style) to define resolution of background images
- improved support for SVG images
- SVG and WMF images supported in background-image
- file attachments
- numeric list-styles added e.g. arabic-indic, bengali, devanagari, persian, thai [CSS3]
- font kerning supported (inter-character spacing between specific pairs)
- letter-spacing and word-spacing supported [CSS3]
- colors supported as rgb(), rgba(), hsl(), hsla(), cmyk(), cmyka(), or spot()
- spot colors supported e.g. PANTONE 310 EC
- PDF/X compatible files
- optionally force use of grayscale, RGB or CMYK color space
- automatic colour conversion for most objects between grayscale, RGB and CMYK

Backwards compatibility

Most changes in mPDF 5.1 are backwards compatible with version 5.0 i.e. your documents should look the same running 5.1. However some changes may alter display from previous versions:

- RTL (right-to-left) languages - see below
- bleed margins when using @page CSS - see below
- Default distance for "cross" from inner margin changed 10->5mm [hardcoded in fn. Footer()]
- If height set on a block element, will force a new page if set-height will not fit on page
- If table rotated, 5mm margin at bottom is now reduced to 1mm
- If image is too big for page and automatically sized to maximum height of page, 10mm margin at bottom reduced to 1mm

Colours may appear more vibrant

Unless specifically set, Adobe Reader uses the RGB colorSpace by default when displaying documents. However

if an image or gradient using transparency (or alpha channel) is included in the document, Adobe Reader

automatically sets the default colorSpace to CMYK - which makes the colours look less vibrant/bright on screen.

mPDF 5.1 now specifies by default a colorSpace RGB for each page, and this will maintain the more

vibrant colours. This is overridden if you use one of the options to restrict the colorSpace (cf.)

RTL

**** IMPORTANT - PLEASE READ IF USING RTL SCRIPTS ****

Handling of RTL (right-to-left) languages has been significantly rewritten, and is likely to cause changes to the resulting files if you have previously been using mPDF. The changes have made mPDF act more like a browser, respecting the HTML/CSS rules.

Changes include:

- the document now has a baseline direction; this determines the
 - behaviour of blocks for which text-align has not been specifically set
 - layout of mirrored page-margins, columns, ToC and Indexes, headers and footers
 - base direction can be set by any of:
 - `$mpdf->SetDirectionality('rtl');`
 - `<html dir="rtl" or style="direction: rtl;">`
 - `<body dir="rtl" or style="direction: rtl;">`
 - base direction is an inherited CSS property, so will affect all content, unless...
- direction can be set for all HTML block elements e.g. `<DIV><P><TABLE>` etc using
 - CSS property `< style="direction: rtl;">`
 - direction can only be set on the top-level element of nested lists
 - direction can only be set on `<TABLE>`, NOT on `THEAD`, `TBODY`, `TD` etc.
 - nested tables CAN have different directions
- NOTE that block/table margins/paddings are NOT reversed by direction
NB mPDF <5.1 reversed the margins/paddings for blocks when RTL set.
- language (either CSS "lang", using Autofont, or through initial set-up e.g. `$mpdf = new mPDF('ar')`) no longer affects direction in any way.
NB `config_cp.php` has been changed as a result; any values of "dir" set here are now ineffective
- default text-align is now as per CSS spec: "a nameless value which is dependent on direction"
NB default text-align removed in default stylesheet in `config.php`
- once text-align is specified, it is respected and inherited
NB mPDF <5.1 reversed the text-align property for all blocks when RTL set.
- the configurable value `$rtlcss` is deprecated, as it is no longer required
- improved algorithm for determining text direction
 - english word blocks are handled in text reversal as one block i.e. `dir="rtl"`
[arabic text] this will not be reversed [arabic text]
 - arabic numerals 0-9 handled correctly

Although the control of direction for block elements is now more configurable, the control of text direction (RTL arabic characters) remains fully automatic and unconfigurable.

`<BDO>` etc has no effect. Enclosing text in silent tags can sometimes help e.g.

`content[arabic text]content`

Justified text

Text-align: justify - no longer uses configurable variable `$jSpacing= C | W | ''`

The default value is for mixed letter- and word-spacing, set by `jSWord` and `jSmaxChar`

If a line contains a cursive script (RTL or Indic [devanagari, punjabi, bengali]) then it prevents letter-spacing

for justification on that line - effectively the same as setting `letter-spacing:0`

Spacing values have been removed from the `config_cp.php` configuration file, so the "lang" property (in `config_cp`) no longer determines justification behaviour (this includes the use of `Autofont()`).

When using RTL or Indic [devanagari, punjabi, bengali] scripts, you should set `CSS letter-spacing:0` whenever you use `text-align:justify`.

@page media

When using @page to create a print publication with page-size less than sheet-size

- bleed margin is now configurable (also crop- and cross-mark margins)
- backgrounds/gradients/images now use the bleed box as their "container box"
- odd-header-name: supports the value "_default" - allows current non-HTML header to remain unchanged
- marks: crop cross; i.e. both together supported
- background-image-opacity and background-image-resize now work with @page CSS

SVG images - extended support

- support for `spreadMethod` property for gradients (repeat and reflect)
- support for `style="font-family; font-size; font-style; font-weight"` i.e. inline CSS
- when `viewPort=""` and `width="" height=""` all specified, uses width to set SVG size of a "pixel"

- support for opacity and multiple "stops" (and colorspace) in gradients

Minor Enhancements

- support for colors as rgb(87%, 56%, 25%) [used especially in SVG]
- added option of "NoPrintScaling" in SetDisplayPreferences
- compress.php - now combines BACKGROUND-IMAGES and GRADIENTS as BACKGROUNDS, and added PROGRESS-BAR
- table with THEAD row will force a new page if no room for the THEAD AND a row from TBODY
- Small-Caps now works properly together with text-align justify
- embedded font subsets restructured (minor) for greater compatibility e.g. with Postscript printers
- PDF/A will convert everything except grayscale to RGB (by default) or CMYK (optionally)

Bug fixes

- Display changed to CMYK colour gamut when document contained an object with transparency set.
Now will retain RGB colorspace (brighter colours)
- If using dir="rtl", tables containing nested tables were not properly reversed
- "text-rotate: 0" set in CSS stylesheet did not 'undo' any text-rotate set on the row (TR)
- Malayalam - character re-ordering
- If height set on a block element, was not taking account of padding top/bottom
- embedded font subsets: error in array of Font Widths fixed
- <style>..</style> containing /* import url() */ the comments were not ignored
- If call mPDF class more than once, error using multiple barcodes or gif files because classes not reinstantiated
- Floating blocks were collapsing bottom/top margins - incorrectly
- Table: if colspan>1 contents are wider than the width of the included columns, did not increase column width(s) to accommodate
- Resizing table - script hanging and new page forced when not required (still)
- If a table style="page-break-inside:avoid" not fit on the page, was adding new page before resizing EVEN IF on a blank page
- End of 2 blocks (e.g. </div></div>) at very bottom of page, forcing unwanted pagebreak
- Corrected handling of tags inside <pre>
- RTL left-aligned text - line ending with
 not correctly left-aligned
- <input type=submit|reset etc name="xxx" e.g. Google button showed as I&039;m feeling lucky
- Annotations all linked to Page 1 (parent object)
- Error "division by zero" using columns
- MultiCell() and Write() [direct writing functions] - miscalculating length of line in non-core fonts (+ other bugs)
- error if CJK space at end or beginning of line with 0x20 spaces in as well

Configurable variables (see config.php file):

```
-----  
$this->printers_info  
$this->bleedMargin  
$this->crossMarkMargin  
$this->cropMarkMargin  
$this->cropMarkLength  
$this->nonPrintMargin  
$this->restrictColorSpace  
$this->PDFX  
$this->PDFXauto;  
$this->useKerning  
[$this->rtlcss removed]
```

Updated files

```
-----  
mpdf.php  
config.php  
config_cp.php (removed references to dir - but not essential to update - just redundant information)  
compress.php  
includes/out.php  
includes/functions.php  
classes/svg.php  
classes/ttfontsuni.php  
classes/indic.php
```

/font/helvetica*.php and /times*.php

Added CSS support

=====

All Block elements including <BODY> <TABLE> <TR>

background-image-resolution: normal | [from-image || <dpi>]
direction: [rtl | ltr] (HTML attribute dir also supported)
background: [gradients]
background-image: [gradients]

For [gradients] syntax see:

- Mozilla linear - <https://developer.mozilla.org/en/CSS/-moz-linear-gradient>
- Mozilla radial - <https://developer.mozilla.org/en/CSS/-moz-radial-gradient>
- Mozilla gradients use - https://developer.mozilla.org/en/Using_gradients
- CSS3 linear gradients - <http://dev.w3.org/csswg/css3-images/#linear-gradients>
- CSS3 radial gradients - <http://dev.w3.org/csswg/css3-images/#radial-gradients>

Almost all elements - block and in-line

font-kerning: auto | normal | none // need to set \$mpdf->useKerning = true;
letter-spacing: normal | <length>
word-spacing: normal | <length>

Colours

Anywhere that color is specified (e.g. color, background-color, borders)

- rgb(255,255,255)
- rgba(255,255,255,1) // last value is transparency (alpha) - between 0-1
- rgb(100%,100%,100%)
- hsl(360,100%,100%) // H: 0-360; S/L: 0-100%; a:0-1
- hsla(360,100%,100%,1)
- cmyk(100,100,100,100) // or 0-100%
- spot(COLOR NAME, 100%) // e.g PANTONE 310 EC; use AddSpotColor() to define first

<TR>

border:

<TABLE> <TR>

background:
background-color:
background-image:

gradient-mask: [can use any of the gradient syntax]
image-orientation: <angle> - supports deg, rad or grad
image-resolution: normal | [from-image || <dpi>]

<OL|UL>

list-style: arabic-indic | bengali | devanagari | gujarati | gurmukhi | kannada | malayalam | oriya |
persian | telugu | thai | urdu | tamil

@page

marks: [crop || cross] - i.e. crop and cross can be used together
odd-header-name: "_default" - allows current non-HTML header to remain unchanged
background-image-opacity: [0-1]
background-image-resize: [1-6] - see Manual

=====

mPDF v5.0 (30/09/2010)

=====

New Features

- Font handling simplified, reads TrueType font files directly

Minor Enhancements

- rotation of fixed-position block elements (see example 10 and manual for supported CSS)
- support for CSS Small-Caps font-variant added
- utility scripts in /utils/ folder to help font management
- new simplified functions AddPageByArray() and TOCPageBreakByArray() added
- progress bar simplified and customisable
- improved word-wrapping for CJK languages
- improved recognition of CJK/Indic/Arabic characters
- invalid UTF-8 input now outputs a meaningful error by displaying input html with errors marked
- GIF or PNG images with transparency/interlaced/non-standard compression handled as internal data if /tmp/ folder is not present or writeable
- support for <html dir="rtl">
- support for "display: none" on inline elements
- annotations supported in fixed-position block elements

Bug fixes

-
 preceded by space does not correctly text-align to right
- zero-width character in middle of line caused line-break (e.g. diacritic or U+200C = ZWNJ)
- HTML attributes not recognised if spaces e.g. 'src = "...'"
- Headers changed for output - problem reported on IE8 64-bit using SSL
- using SetAutoPageBreak(false) used caused unexpected behaviour with table rows at page break
- (from Beta) incorrect check for temporary font data folder causing errors
- artificial Bold/Italic not working in table cell when using rotated text
- allow <dottab> to inherit font color correctly
- SVG now works with Adobe 7
- background in header overwriting text
- vertical text in table header not correctly horizontally positioned when repeated
- compatibility with PHP >= 4.3 (htmlspecialchars_decode, stripslashes)
- updated deprecated script PHP 5.3.0 (\$string{1} to \$string[1], \$var =& new Object(), set_magic_quotes_runtime)
- index (CreateIndex) number string incorrect if arabic(rtl) text anywhere in document
- MultiCell incorrectly calculate string length/width when using core fonts
- page-break-inside:avoid - used with non-HTML footer had space inserted for footer height
- page-break-inside:avoid - error if more than 1 page height but not enough to trigger second pagebreak
- page-break-inside:avoid - incorrectly layering page backgrounds (headers and content brought forward)

Changes from 5.0 Beta

If you are upgrading from the Beta version - you MUST delete all files in the /ttfontdata/ temporary directory

- config.php file has been changed (extra CJK characters to recognise CJK blocks)
- \$this->backupSubsFont (in config_fonts.php) optionally now takes an array
- no need to define 'cjk'=>true or 'sip|smp'=>true in config_fonts.php (ignored; cf. \$this->BMPonly)
- Indic language fonts have been altered to add Latin and Latin-1 Supplement characters
- progress bars now has an external progbar.css and configurable main heading
- added initial parameter new mPDF('+aCJK') or '-aCJK' to override default useAdobeCJK at runtime
- QRCode is not included in main download (but as an extra package)

BACKWARD COMPATIBILITY

If you have been using earlier versions of mPDF, most scripts should work as before. But note:

- Arial, Helvetica, Times and Courier are now treated like any other font
- the whole CSS font string is parsed e.g. style="font-family:'Lucida Grande';" will look for a font 'lucidagrande' and not 'lucida'

Configurable variables (see config.php file):

- \$mpdf->useSubstitutionsMB is now deprecated, but will work as an alias for \$mpdf->useSubstitutions
- The initial parameters e.g. new mPDF('utf-8') have all changed. Old ones may be recognised, or will be ignored.
- \$mpdf->useOnlyCoreFonts is now deprecated and is ignored. Use new mPDF('c')
 - \$this->use_CJK_only is now deprecated and is ignored. See \$this->useAdobeCJK and new mPDF('+aCJK') or '-aCJK'

```

Control SmallCaps appearance
- $mpdf->smCapsScale = 0.75;      // Factor of 1 to scale capital letters
- $mpdf->smCapsStretch = 115;     // % to stretch small caps horizontally
Customisable Progress bar
- $mpdf->progbar_heading = 'mPDF file progress';
- $mpdf->progbar_altHTML = '';
Control fonts/subsetting
- $mpdf->maxTTFFilesize = 2000;
- $mpdf->percentSubset = 30;
- $mpdf->debugfonts                // show font errors and warnings
Replaceable alias
- $mpdf->iterationCounter = false;  // Allow use of {iteration varname} in THEAD

=====
mPDF v5.0Beta   (21/07/2010)
=====

New features
-----
The main change in mPDF v5 is the handling of TTF and TTC fonts directly.
See README.txt and FONT INFO.txt for more information

QR-code (2-dimensional barcode) Added
-----
type="QR"
Size=1 is an arbitrary 25mm widthxheight. error="L|M|H|Q"
text="" can be numeric, alphanumeric or binary(?)
Required whitespace is always included around it

Enhancements
-----
- progress-bar is simplified (no javascript class)
- dir="rtl" supported in <html> or <body> tag

Bug fixes
-----
- artificial Bold/Italic now working in table cells with rotated text
- "-" is now allowed in a font name e.g. sun-exta
- <dottab> now inherits font color correctly
- SVG class bugs fixed (was crashing in Adobe Reader v 7)
- background color/image in header no longer overwrites the header text

Changed Config variables
-----
$this->useSubstitutionsMB is depracated
Character substitution always occurs when using core fonts.
Use $this->useSubstitutions for all cases.

New Configurable variables
-----
$this->useAdobeCJK = true;          // Uses Adobe CJK fonts for CJK languages
                                // default TRUE; only set false if you have defined some available fonts that
support CJK
                                // If true this will not stop other CJK fonts if specified by font-family:
                                // and vice versa i.e. only dictates behaviour when specified by lang="" incl.
AutoFont()

// Set maximum size of TTF font file to allow non-subsets - in kB
// Used to avoid e.g. Arial Unicode MS (perhaps used for substituteCharsMB) to ever be fully embedded
// NB Free serif is 1.5MB, most files are <= 600kB (most 200-400KB)
$this->maxTTFFilesize = 2000;

// If not -s (i.e. forced subset) this value determines whether to subset or not
// 0 - 100 = percent characters
// i.e. if ==40, mPDF will embed whole font if >40% characters in that font
// or embed subset if <40% characters

```

```
// 0 will force whole file to be embedded
// 100 will force always to subset
$this->percentSubset = 30;

$this->debugfonts - show errors and warnings for font parsing

Config variables removed
-----
$this->use_CJK_only
$this->useOnlyCoreFonts

=====

====
4.6
====

mPDF

files changed:
mpdf.php
config.php
makefonts/makefonts.php
class/tlasm.php
class/svg.php
graph.php

examples_04 (images)

config var added:
$this->tableMinSizePriority

4.5.015
Bug fix:
Complex page with ToC entries ++ (example_ToC_bug4_5_015.php) caused Apache to crash
AdjustHTML() preg_pattern for matching <hx>... </hx> <table for keep-together - altered and fixed ?
matching
Seemed to crash when content="Graph 12" between the <h> - 2 numbers (12) crash, 1 didn't!!!

4.5.014
Bug fix:
Using TrueType fonts, unused font is not embedded in the PDF doc. This was fine except an error
message appeared after printing in Adobe Reader,
because Font reference /F1 still present in doc pointing to non-existent resource.
Edited so that the reference is now removed from the page if font unused.

4.5.013
Enhancement
TrueTypeUnicode fonts width array inserted as shortened form array (smaller file size)

4.5.012
Bug fix: Incorrect handling orphan characters in table
(cf. http://mpdf.bpm1.com/forum/comments.php?DiscussionID=193 fixed in 4.2 - but going back to it
still problems)
If xxxxx. fits but xxxxx.. doesn't: WriteFlowingBlock wraps it to next line, TableWordWrap squeezed it
onto one line
TableWordWrap fixed to only allow one orphan char. even if it fits with that one.

4.5.011
Added Windows BMP image support

4.5.010
SVG class:
- improved recognition of lineargradients/radialgradients referenced by xlink:href
- does not die if empty text string
- support for many text properties as style="" as well as currently as attributes (bold, fill etc)
- if using MB font, was respecting "Times" and "Courier" from the SVG file but using as ANSI not utf-8
```


4.5.009

graph.php updated to include SVG - need to define in graph.php (as well as set up TTF fonts)
(SVG graph does not include CSIM, 3D skew.)

4.5.008

tlasm.php has an error in the error message if .dat fontfile not found (".char.dat")

4.5.007

Bug fix: Using page-break-inside:avoid, if nothing would have been printed on page 1 before next page, elements going all over the place!

Also problem shifting images - fixed

Also wasn't shifting WMF/SVG images - fixed

4.5.006

New config var

`$this->tableMinSizePriority = false;`

If page-break-inside:avoid but cannot fit on full page without exceeding autosize; setting this value to true will force respect for autosize, and disable the page-break-inside:avoid

[NB edit Manual Table>>autolayout algorithm]

4.5.005

Bug fix

Table set to avoid page-break-inside: in some circumstances entered loop with recalculating size
Fudge factor added of 0.001 in tbsqrt to calculate shrink factor

4.5.004

Bug fix

If table set to avoid page-break-inside and table height (resized) exactly==remaining page - was triggering page break

Fudge factor added of 0.001 in tablewrite to query pagebreak

4.5.003

Bug fix in makefonts/makefonts.php

Also changed the links in Step4 & 8 which move the newly created files to the font directory - will now show error message if error -

will NOT overwrite existing files. (Put in manual already)

4.5.002

Bug fix in class/tlasm.php

If you have magic_quotes_runtime set On - problems using embedded subset.

4.5.001

JPG "Exif" file recognised from header, and handled much more quickly and efficiently (not using GD)

=====
mPDF v4.5 (21/04/2010)
=====

New Features

The main change in 4.5 is the improved class for importing SVG images. (See details below)

Font files

Some bugs in the "makefonts" utility caused some errors in the files produced for embedding font subsets.

Surprisingly these are not easily detectable (I have yet to find one!).

All the font files used for embedding font subsets (the .dat and .dat.php files in /unifont/ folder) have been re-generated. Download them if you are having problems with any fonts - otherwise, you probably

don't need to bother.

Minor Enhancements

If keepColumns = true (i.e. disable readjustment of column length), mPDF will now reproduce table header/footer rows in each column [4.4.015]

A number of changes to improve processing time [4.4.012]
[Thanks to carlholmberg http://mpdf.bpm1.com/forum/comments.php?DiscussionID=274&page=1#Item_3]

JPG files with header marked as "progressive DCT-based JPEG" are now supported [4.4.004]

Configurable variable (config.php) \$dpi can be set to vary size interpreted from "px" values in HTML/CSS

NB Recommended that \$dpi should always be set the same as \$img_dpi

Support added for "ex" as a size value (approximates "ex" as half of font height)

Configurable variable (config.php) \$watermarkImgAlphaBlend will determine how watermark images will blend with underlying objects.

Bug fixes

- Make-fonts utility : makefonts/makefonts.php [4.4.016]
(All font files have been updated)
- Table header of only one column width - not printing right border [4.4.014]
- WMF and SVG images not rotating correctly to 90 or -90 degrees [4.4.013]
- Using templates, error if imported doc contains templates itself [4.4.001]

Updated Files

mpdf.php
config.php
classes/svg.php
makefonts/makefonts.php
ALL subset font files (/unifont/ .dat and .dat.php files), and all garuda and norasi files

New files

None

New config variables

\$this->watermarkImgAlphaBlend
\$this->dpi

BACKWARD COMPATIBILITY

All but one changes in mPDF 4.5 are fully backwards compatible.
The configurable variable \$this->watermarkImgBehind was introduced in v4.4 and was unintentionally set to TRUE
In v4.5 this is set to FALSE in the config.php file.

SVG Images

[svg.php CHANGED]

- Text stroke-width default changed to 1 [4.4.011]
- Text stroke - line-join type changed [4.4.010]
- Default value for fill changed to "black" [4.4.008]
- Bug fixes:
 - * to correct calculation of text-length (and therefore alignment R and C) [4.4.009]
 - * Corrected errors in path implementation esp. quadratic Bezier curves
 - * rounded corners to rectangles - error corrected
 - * Recognition of font-family improved
 - * remove \n (and other non-printable chars) from text
 - * zero length shapes are not output e.g. zero-width rectangle, zero-length line, zero-radius circle
- Support added for:
 - * gradient stop offsets and gradientUnits="userSpaceOnUse" [4.4.007]
In mpdf.php enabled define inner radius for radial gradients - only used internally by SVG at present
 - * user defined <ENTITY /> cf. 'render-elems-03-t.svg' in SVG Test Suite [4.4.006]
 - * "color" attribute and "currentColor" value for fill and stroke [4.4.005]
 - * fill:url(#...) in a style as well as attribute
 - * xlink:href for gradients

- * 1.3002e-005 in svg path
- * text-style changes (e.g. text-anchor) set on <g> element - not just on <text>
- * fill-rule=evenodd|nozero
- * dashed lines / stroke-dasharray & stroke-dashoffset
- * gradientUnits=userSpaceOnUse;
- * units e.g. 3mm or 14pt in Rectangle, Circle, Ellipse, Line and Text position
- * transform on <text> element
- * stroke as well as fill on text

NB The following are still NOT supported for SVG

- filters
- <marker>
- images
- DOM
- <pattern>
- textlength; lengthadjust; tspan, tref, toap, textPath;
- <use ../>
- gradient on stroke/text;
- <clipPath>
- text-underline and strikethrough
- text opacity
- colors as rgb(87%, 56%, 25%)
- rect using units for dimensions
- Only uses default spreadMethod = "pad" for gradients

```
=====
mPDF v4.4    (24/03/2010)
=====
```

New Features

- Support SVG image files (partial)
- Rotate images or graphs (by multiples of 90 degrees)
- Set opacity (transparency) for background images
- Control resizing of background images
- Set whether to print watermark images behind or in front of page contents
- Reduced memory usage when printing tables (partly configurable)
- Option to set path to folder for temporary files
- Improved compliance for CSS text-align justify
- Increased support for CSS "media"
- Improved performance when accessing local image files

Minor Enhancements

- Allows space in output file name e.g. \$mpdf->Output('t est.pdf','D'); [4.3.007B]
- Header changed in Output to improve compatability with IE6 (affects 'D' and 'I') [4.3.012B]
- background-images do not show noimage.jpg if missing [4.3.012D]
- simpleTables (which improves performance) now also allows: background-color, -gradient and -image, padding and rotated text to be set for each cell. Only borders are not supported cell-by-cell. [4.3.006]

Bug fixes

- Page width not correctly reset when defining default page margins (L/R) by @page [4.3.007C]
- Table row <TR> with a background-color, paints the whole row, including the spaces between cells [4.3.005]
- NB This should have been fixed in [4.2.028] but got left out!
- UseSubstitutionsMB causes errors inside <textarea> and <select> so now disabled in these 2 situations [4.3.004]
- CSS background: 'none' did not cancel background-image/background-color if it comes later [4.3.002, 4.3.011]
- Warning message 'depracated' (as of PHP 5.3) when using Templates [4.3.007]
- AutoFont incorrectly altering multibyte characters ending in \xa0 [4.3.012C]
- "Initial" default value for border-width changed from 1px to 'medium' e.g. border-top: solid

#000000; [4.3.010]
- WMF image sometimes inverted [4.3.016]

Updated Files

mpdf.php
config.php
changelog.txt

New files

classes/svg.php

New config variables

\$this->justifyB4br=false;
\$this->CSSselectMedia='print';
\$this->watermarkImgBehind = false;

BACKWARD COMPATIBILITY

All changes are backwards compatible except the handling of some background-images - please see notes below.

Watermark Image z-order

By default mPDF prints watermarks on top of the page contents to ensure that they are not hidden by backgrounds (especially table cells).

You can specify watermark images to be printed behind page contents by setting a configurable variable:

\$this->watermarkImgBehind = true; // default=false
[4.3.018]

Rotating Images and Graphs

Images or graphs can be rotated (by multiples of 90 degrees) using a custom HTML attribute e.g.

<jpgraph rotate="90" ... />

Valid options are: 90|-90|180.

Positive values are clockwise.

If width is specified e.g. width="3cm" this is applied to the rotated image i.e. will be width 3cm after rotating

[4.3.016]

Background Image Opacity

A custom CSS property "background-image-opacity": is now supported on BODY, DIV+ (block elements) and TD

Takes values between 0 and 1.0

Resizing Background Images

A custom CSS property "background-image-resize": is now supported on BODY, DIV+ (block elements) and TD

0 - No resizing (default)

1 - Shrink-to-fit w (keep aspect ratio)

2 - Shrink-to-fit h (keep aspect ratio)

3 - Shrink-to-fit w and/or h (keep aspect ratio)

4 - Resize-to-fit w (keep aspect ratio)

5 - Resize-to-fit h (keep aspect ratio)

6 - Resize-to-fit w and h

N.B. Prior to v4.4 background-images were incorrectly constrained to maximum width of the containing

block.

The default is now to do NO resizing on background-images. Setting "background-image-resize:3" should be used

for backwards compatibility.

[4.3.015, 4.3.012D]

SVG Image files

SVG image files are now partially supported (but as for WMF - not as background-images).

viewBox (preserveAspectRatio is not supported) viewBox="0 0 400 200" width="400" height="200"

Takes viewBox in preference to width/height if present on <svg>

If neither present, will size to width of page (square) as the containing box.

Units are interpreted as pixels if undefined.

Doesn't recognise internal CSS <style> elements

Gradients only take 2 colours which are taken as stop-offset 0% and 100%

[4.3.013 & 4.3.017]

Reduced Memory Usage printing Tables

mPDF uses a lot of memory when processing large tables. Parts of the script have been rewritten to reduce memory consumption when writing tables which use collapsed borders (10-25% saving).

Memory usage can be reduced further by setting a configurable variable:

`$this->packTableData = true; // default=false`

but note that this causes a significant increase in processing time.

[4.3.008, 4.3.019, 4.3.014]

User-defined path to Temporary folder

mPDF uses a folder to write and store temporary files when processing images. By default this is the [your_path_to_mpdf]/tmp/

This is now user-definable by defining the constant `_MPDF_TEMP_PATH` before including mpdf.php script.

Text Justification

In a justified text block, an inline image, textarea, input, or select causing a new line will now force

the previous line to be justified. HR and BR do NOT force justification (as in browsers).

For optional compliance of MS Word behaviour, there is a new configurable variable:

`$this->justifyB4br = false; // Change to true to force justification before a
 (as in MS Word)`

[4.3.003]

CSS support for @media

Now supports media-dependent CSS styles e.g.

`@media print {`

`p { color: red; }`

`}`

as well as

`<style media="...">...</style>` and

`<link rel="stylesheet" media="print" href="..." />`

Proper matching of CSS media to select using configurable variable:

`$this->CSSselectMedia='print'; // default="print" set in config.php : screen, print, or any other CSS @media type (not "all")`

N.B. `$this->disablePrintCSS` is now deprecated

[4.3.001]

NEW FEATURES

- Page (sheet) size can be reset within document (<http://mpdf1.com/manual/index.php?tid=436>) [4.2.024, 4.2.025]
- PDF/A1-b compliant files (<http://mpdf1.com/manual/index.php?tid=420>)
- Improve performance using simpleTables (<http://mpdf1.com/manual/index.php?tid=430>)
- mPDFI incorporated into main mPDF class (<http://mpdf1.com/manual/index.php?tid=432>)
- <dottab> added as custom HTML tag: inserts dots to the following text, which is right-aligned [4.2.031]

See Example files 38 and 39 for PDF/A compliant file and <dottab>

BACKWARD COMPATIBILITY

All changes are backwards compatible except the use of mPDFI. You will need to make minor changes to your scripts.

See the manual <http://mpdf1.com/manual/index.php?tid=432> for details.

BUG FIXES

- When using Table of Contents and not resetting page numbers: HTML headers/footers showed incorrect page number [4.2.020]
- Table of Contents: last page not printing page background-color [4.2.023]
- Image file with space " " in the file name failing [4.2.016]
- Image file path unnecessarily resolved to full URI - changed to use relative path if possible [4.2.029] ***
- Table - not calculating height of cell correctly [4.2.015, 4.2.012, 4.2.011, 4.2.009]
- Table row breaking after/during cell when image in cell taller than font-height [4.2.008]
- When Table row(cell) greater height than the page-height but requiring resizing greater than allowed by autosize - not resizing [4.2.005]
- Table cell border not resized correctly [4.2.002]
- Table row <TR> with a background-color, paints the whole row, including the spaces between cells [4.2.028] ****
- Background-image in HTMLFooter not correctly setting 0,0 origin [4.2.014]
- Background-image set as an in-line style not working [4.2.013]
- Background-image set in CSS @page or <body> was being constrained to less than page size [4.2.032]
- Imported Templates overwriting Headers (with images or gradients) [4.2.004]
- When using imports/templates, HTML header with background-image causing page to disappear [4.2.001]
- block-style element breaking over more than 2 pages incorrectly adjusting L/R margins [4.2.022]
- CSS @page property "size" set on :left :right or :first pseudo-selectors - disabled [4.2.022]
- Annotations default colour incorrectly set in PDF as [100 100 0] corrected to [1 1 0] (seemed to work ok?) [4.2.026]
- Overwrite() now parses input file more tolerantly recognising more source files [4.2.030]

**** Bug fix 4.2.028 never got into the release of v4.3 Included in next release [4.3.005]

**** Bug fix 4.2.029 never not fully implmented in v4.3 Included in next release [4.3.012]

Changed files

mpdf.php
compress.php
config.php
classes/tlasm.php
includes/functions.php
mpdfi/fpdi_pdf_parser.php
Added files/folder: /mpdfi/filters/*.*
Added file/folder: /iccprofiles/sRGB_IEC61966-2-1.icc
mpdfi/mpdfi.php (no longer required)

New Configuration variables

[config.php]
\$this->enableImports
\$this->simpleTables
\$this->PDFA
\$this->ICCProfile
\$this->PDFAuto

Minor changes

Increased PDF file compatibility with spec 1.4

- PDF version changed to 1.4
- A binary file marker (a comment line with 4 characters > 127 ASCII) is added just after the first line
- %%EOF no longer has line break after it [4.2.010]
- /ID object is added to trailer object when not encrypted [4.2.010]

When using progress bars, one of the JS scripts is now referenced as an external file to allow it to be cached by user's browser and improve performance for end-user [4.2.007]

Importing external PDF files: LZW encoded PDF files are now supported

When adding an annotation, the popup window can be set to be either open or closed when the document is opened [4.2.027]

- size and position of the popup can also be specified

=====
mPDF v4.2 (27/01/2010)
=====

NEW FEATURES

- image handling improved
- table layout - additional control over resizing
- vertical-alignment of images - better support for all CSS types
- top and bottom margins collapse between block elements
- improved support for CSS line-height
- display progress bar whilst generating file
- CSS @page selector can be specified when adding a pagebreak
- CSS @page selector allows different margins, backgrounds, headers/footers on :first :left and :right pages
- PNG images with alpha channel fully supported
- ability to generate italic and bold font variants from base font file
- CJK fonts to embed as subsets
- "double" border on block elements
- character substitution for missing characters in UTF-8 fonts
- direct passing of dynamically produced image data
- background-gradient and background-image can now co-exist

Bug fixes

- empty variable (undefined var, false, null, array() etc.) sent to WriteHTML produced error message "Invalid UTF-8"
- CJK in tables when not using CJK (utf-8-s) autosized very small as characters did not word-wrap
- parsing stylesheets: background image not recognised if contained uppercase characters in file name
- "double" border on table used white between the lines instead of current background colour
- \$this->shrink_tables_to_fit = 0 or false caused fatal errors
- background color or images not printing correctly when breaking across pages
- background not printed for List inside a block element
- columns starting near end of page with no room for a line triggering column change (resulting in text misplaced) not page break
- table cell not calculating cell height correctly when "orphan" characters (;,.,?! etc.) at end of line
- table breaking page in column 2 when col 1 is rowspan'ed
- margin-collapse at top of page not working if bookmark/annotation/indexentry/toc
- column break triggered by HR triggering a second column break
- an empty 'position:fixed' element with no/auto width or height caused fatal error
- mPDFI: template documents were overwriting HTML headers
- mPDFI: function Overwrite (to change text in existing PDF) - fatal error if using with encrypted file

Bug - not fixed

- WriteHTML('',2) with '2' parameter not recognising 'margin-collapse:collapse' for DIVs or 'line-height' set in default CSS 'BODY'

New or Updated Files

mpdf.php
compress.php
config.php
config_cp.php
config_fonts.php
mpdf.css
classes/gif.php
classes/indic.php
includes/subs_core.php
mpdfi/mpdfi.php
unifont/ar_k_001.uni2gn.php
All files in new folder: /progress/*.*

NEW FOLDER /tmp/ required with read/write permissions - used for temporary image files or progress bars

=====
mPDF v4.1.1 (21/12/2009)
=====

Error corrected in /makefont/makefonts.php file (moved completed Unicode files to font folder instead of unifont)

=====
mPDF v4.1 (20/12/2009)
=====

MySQL support for embedded font subsets abandoned, and replaced with file-based.

Files no longer required

config_db.php
/unifont/RUNME.php
/unifont/*.ufm and /unifont/*.tla font files

MySQL Database no longer required

Files Updated

mpdf.php
/classes/tlasm.php
/makefont/makefonts.php

New files

/unifont/*.dat and /unifont/*.dat.php font files

Bug-fixes

- Image - If automatically resizing to fit maximum page size incorrectly subtracted margin-header
- Annotation and textarea in same HTML chunk causes mPDF to crash (preg_replace textarea with /u modifier in AdjustHTML)
- set_magic_quotes_runtime error (\$mgr not \$mqr)
- Table align did not reverse when using RTL document

Alteration: Image - if writing Image in fixedpos div position:absolute - to allow Image to be resized to full page size

=====
mPDF v4.0 (17/12/2009)
=====

Major additions

- Ability to embed font subsets (creating much smaller files)
- Much improved support for Arabic languages
- Support for Indic languages including consonant conjuncts
- Support for Fixed position block elements
- New utility to help create your own fonts
- PNG alpha channel transparency supported
- New utility to create smaller mpdf script with reduced functionality (less memory)
- Multiple Barcode types supported

 * For more details see the documentation manual: <http://mpdf1.com/manual/index.php?tid=410> *

Bug fixes (parsing CSS)

- <link href="" ... was not recognised if > 1 space between words
- #Content p em { font-style:italic; } was applied to "#Content p"
- @import url() embedded in a stylesheet file requires path fixed relative to stylesheet file
- background-image url() embedded in a stylesheet file requires path fixed relative to stylesheet file
- comment tags inside CSS <style> embedded in the HTML were removed
 Now fixed so <style><!-- ... --></style> works; <!-- <style>...</style> --> is removed

Bug fixes (other)

- clear (CSS property for floating elements) caused properties for that element to reset to defaults
- width: auto caused collapse of border and padding on L & R of ordinary block elements
- text-indent not inherited correctly (including em and % values)
- named colour "steelblue" corrected RRGGBB hex code
- table cell widths in %: if width of table cells set to >=100%, and not all columns are set
 This was fixed in 3.2 but led to problem where 2 cols: 1) 80% and 2) not set (see Table sizing test)
 Now fixed again to work for both(?)
- parse PNG error fixed
- background-image not correctly positioned in HTMLFooter and HTMLHeader (Not fixed properly in 3.2!)
- fonts not supported with 0-9 in the name
- font list in GetCodepage() in htmltoolkit.php (now config_cp.php) containing space " " not recognised
- list number positioning
- list font size set in CSS for UL/OL not working for first level list
- table width (real value, not %) not working in nested table
- GIF file failed if PDF file not compressed
- list-style-type incorrectly inherited
- line-height inheritance in lists
- SetColumns added a new line - not required if at start of document/page
- footer_line_spacing did not work
- table cellPadding="" overwrote cell padding set on cell CSS
- could not turn off Default non-HTML footer LINE
- border specified as "em"
- default values set in mpdf.css overridden by inherited properties e.g. <div><h1>Here</h1></div> lost font-size for H1

=====
 mPDF v3.2 (25/10/2009)
 =====

Bug fixes

- Table cell widths in %: if width of table cells set to >=100%, and not all columns are set -> froze, because tries to produce a column of no width
- Output download file changed to allow compatibility with IE6
 (http://mpdf.bpm1.com/forum/comments.php?DiscussionID=120&page=1#Item_4)
- Image error if relative path used on domain root (e.g. img src="image.png" and basepath is <http://www.yourdomain.com>) [attempted fix in 3.1 not working]
- Table: if font changed in cell, font was not restoring properly afterwards causing errors (restoreInlineProperties())
- Lists: list items containing
, font not restoring after bullet
- Graceful support for block elements inside list items e.g. <p>... (not supported, but tolerated)
- Index: Created dividing letters separately for Uppercase and lowercase
- Incorrectly changing input character set when encountering e.g. charset=iso-8859-1 in the text of

the document

- Changed so only detects it if within <head>...</head>
- If Keep-with-table (i.e. H1-6 before table and use_kwt true), if pagebreak forced anyway, borders did not print on previous page
- Background-image used in HTML footer not appearing (correctly)
- RTL tables: nested tables will not automatically transpose L->R
- "Keep heading with table" - changed to allow <h1 style=".."> not just <h1>
- "Keep heading with table" - backgrounds (bgcolor, image or gradient) incorrectly handled - now removed
- Rotated table spread over more than 1 page caused enclosing block background colours to be be rotated along with table
- CSS text-indent % now correctly supported (% of containing block width)
- CSS width em on a block element e.g. DIV now correctly supported
- calculating _tableheight, if remainingpage==0, get error (div by zero)
- Table moved to next page with page-break-inside=avoid, produced an enlarged table (font)
- RTL text-align override on BODY text was not working consistently
- Arab characters: Character ه (HEH) appearing in Final presentation form instead of Isolated
- Vertical position of background-image on whole page incorrect
- SetProtection can now be used with no permissions set (was not working unless at least one permission set)

Developers

Some more undefined indexes and variables declared (courtesy of DSmart
http://mpdf.bpm1.com/forum/comments.php?DiscussionID=117&page=1#Item_0)
Comment lines removed for < v3.0 to tidy up code

Enhancements

CSS style height now partially supported on block elements DIV, P, H1 etc. --IF--

- block is all on one page
- will extend the block but not shorten it
- will not force a pagebreak (max. at bottom of page)
- % is interpreted as % of printable page height (inside margins)

<TF00T> now supported (placed at start as in HTML spec) displays at end of table, and repeats as a footer

Background-image and background-gradient now supported in TD and TH (works in all cases except:
background-image is not rotated or
positioned correctly if table is rotated)

NB Background images and background-gradients do not work if Columns are being used, or if \$use_kwt is TRUE (keep-with-table),
or if page-break-inside:avoid is active.

Updated files

mpdf.php
htmltoolkit.php

=====
mPDF v3.1 (30/08/2009)
=====

Bug fixes

- Image error if relative path used on domain root (e.g. img src="image.png" and basepath is <http://www.yourdomain.com> was giving <http://www.yourdomain.com//image.png>) [3.1]
- Errors in parsing background CSS (background-repeat, background-position etc) [3.1]
- Textarea did not correctly convert width or height in units relating to font e.g. em [3.0beta_01]
- If page margin-bottom set to zero, SetHTMLfooter() crashes with "Division by zero" error [3.0beta_01]
- Table with header row and rowspan in tbody, not calculating maxrowheightcorrectly
- Prevent Index breaking column just after a dividing letter
- Select or input form field when text around it is justified had text in the form field justified

- TocBookMarkText needs to be htmlspecialchars-ed - decoded when entered inside <tocpagebreak>
- caused crash
- DisplayPreferences used as a variable name and a function: function renamed to SetDisplayPreferences()
- Image with src file not including a "." incorrectly parsed (e.g. <http://www.domain.com/imagegenerator?params=23>)

New Features

- var \$debug (true|false) default false; show or hide error reporting at output stage [3.1]
- var \$autoPageBreak (true|false) default true; allows overriding of automatic page breaks [3.0beta_02]
- <indexinsert /> HTML equivalent of CreateIndex() [was CreateReference()]
- 2nd attribute/parameter "xref" in IndexEntry() and <indexentry> - works like IndexEntrySee() as cross-reference entry
- function SetWatermarkText allows null parameters to be passed i.e. SetWatermarkText() - will clear the WatermarkText
- <watermarktext content="" alpha="" /> - HTML equivalent of SetWatermarkText()
- <watermarkimage src="" alpha="" position="" size="" /> - HTML equivalent of SetWatermarkImage()

Documentation

See Manual at <http://mpdf.bpm1.com/manual/> for more information - especially:

- User's Guide>>What Else Can I Do?>>Backgrounds & Borders
- User's Guide>>What Else Can I Do?>>Floating blocks

Files updated:

- mpdf.php
- htmltoolkit.php
- graph.php

Developers only

mPDF<=3.1 generated a large number of warning "Notices" if run with full error_reporting on, due to array indexes not being initiated e.g.

```
$arr = array();  
...  
if ($arr['index'] == 5 ) {...}
```

To prevent this, lines were added at the start of the mpdf.php script to turn error notices OFF. In a move towards making mPDF able to run with full error_reporting on, a large amount of the script has been altered e.g. the line above would be changed to:

```
if (isset($arr['index'] && $arr['index'] == 5 ) {...}
```

Although I have tested this with a number of examples, it is almost certainly not complete. Therefore the error_reporting for Notices is still turned off in mPDF 3.1. If you care to test it, please uncomment line 43 (//error_reporting(E_ALL);) and report any warning notices that you get. NB This has added about 40kB to the script size.

```
=====
mPDF v3.0beta  (14/06/2009)
=====
```

New Features

- CSS "float" partially supported (as well as clear:left|right|both)
- CSS "background-image" "background-position" "background-repeat" "background-color" "background" supported for block-level elements
- CSS background-color and background-image for <body > element added: this covers the whole page i.e. not just inside the "margins"
- CSS background-color and background-image can be defined for CSS @page{}
- Background gradients (linear or radial) can be defined using a custom CSS style property

- Border radius can be defined to give rounded edges to block elements (uses draft CSS3 spec.)
- page number can be reset to any value during the document (in AddPage() <pagebreak> etc.)
- PNG images: Interlaced and alpha-channel-set PNG images now supported
- internal links supported in Indexes (parameter added to CreateIndex()/CreateReference(): \$useLinking=true;)
- HTML Headers and footers now support hyperlinks
- improved handling of
, block elements, and text lines inside table - approximates better to browser handling
- borders of block-level elements & table cell borders supported (partially) in columns
- optional error reporting for problems with Images (\$showImageErrors)
- ToC will word-wrap long entries
- internal links (Bookmarks, IndexEntry and ToCEntry) rewritten to give more accurate positioning (when used as <tag>)
- autofont algorithm improved for CJK languages
- define text before and after page numbers (\$pagenumPrefix; \$pagenumSuffix; \$nbpPrefix; \$nbpSuffix;)
- Additional color names supported - full list from SVG1.0

Bug fixes

- Column width not resetting after an automatic pagebreak, or after setting HTMLheader
- using AutoFont unnecessarily changed htmlspecialchars to code causing errors
- Lists inside a table - incorrectly calculating table cell height
- CJK - 4-byte utf-8 chars not displaying properly (includes HKCS characters)
- mailto: links incorrectly handled
- TOCpagebreak() - usePaging default clarified: true unless specified as '', 0, '0' or false; (null -> true)
- <tocpagebreak> (as html tag) with no "name" defined, used at start of page, added a further blank page(s)
- Lists - inaccurate calculation of space required for numbers in certain circumstances
- Generated images (.php) only working if cURL enabled - (fixed, but requires allow_url_fopen if remote file)
- flag added to turn off error reporting when buffering used (\$allow_output_buffering = false;)
- RTL text in Bookmark, Title, Author, Creator, Keywords, and Subject was reversed - Adobe Reader 9 now correctly handles RTL text (which Reader 8 did not)
- TOC - if not using ODD/EVEN paging, did not add extra page and messed up
- Rotated table which did not fit on remaining page resized to bigger than default
- HR of width less than 100% - text continued on line after it
- HR alignment not working (fixed so both CSS text-align and margin: 0 0 0 auto etc work)
- HR in table did not correctly re-size when necessary
- characters in symbols/zapfdingbats which in non-utf-8 mode are represented as chr(173) incorrectly handled as soft-hyphens
(bug introduced 2.5 with soft-hyphens - affects symbols ↑ arrow-up and Zapfdingbats ② encircled 2)
- Internal links (anchors) - Annotation/Bookmarks etc. incorrectly positioned when page orientation changed
- ToC - when using multiple ToCs, internal links were not correctly adjusted
- anchor (a name="") used inside a table was incorrectly positioned at the end of table
- Tables: cell height calculated incorrectly when BR used
- Table rotated with "page-break-inside:avoid" not kept on one page
- Table rotated and split over > 1 page - vertical alignment inaccurate
- Headers/Footers (non_html) when no style set caused errors
- Table: breaking page when using rowspan error (line 17142)
- ToC: If no indent defined in HTML tag <tocpagebreak> or defined as 0 gave error

Note

In mPDF 3.0 the following sections of code have been significantly rewritten:

- painting of borders and background colours for block-elements
- table of contents
- Index
- vertical justification in columns (uses scaling to stretch vertically)

NB changed htmltoolkit AdjustHTML - does not now remove
 before </div>
Warning - may display differently in normal text as well as tables

Files updated:

mpdf.php

htmltoolkit.php

Developers only

- Background-color handling in CSS changed so only inherited/cascaded when Columns active or Keep-block-together
 - otherwise would overwrite background image with inherited color
- all %.2f used in sprintf() changed to %.3f in htmltoolkit.php and mpdf.php to increase accuracy of div border lines in columns etc.
- variable \$use_embeddedfonts_1252 renamed to \$useOnlyCoreFonts as more precise: depracated but still supported.
- this version included quite abit of tidying up/future-proofing some code:
 - \$var{0} changed to substr(\$var,0,1) etc. (due to go in PHP6)
 - ereg_ changed to preg_ (depracated in PHP5.3) - (NB mainly in htmltoolkit.php)

=====

mPDF v2.5 (01/05/2009)

=====

New Features

- Automatic Hyphenation added, and support for soft-hyphens
- Encryption works now for CJK language documents
- Improved text justification
- Support for 'generated' images e.g. "../onthe-fly-image.php"

Bug fixes

- Tables: cell height did not reduce if font-size used was smaller than table default
- Columns: if setcolumns() to the same number already active - did not print out last bit of previous columns
- Page-break in the middle of a block caused incorrect margin and padding on next lines until end of block (\$cMargin reset to 0 in AddPage)
- <HR> in table cell was printing in incorrect position (bug introduced in mPDF 2.4)
- Justification
 - if only one word on line, did not respect maximum character spacing
 - last character of line incorrectly had character spacing applied
 - Space at the end of last line of a Right Justify block - e.g. "end. </p>" now correctly ignored
 - incorrectly treated as a character when justifying text with word/char spacing
 - CJK punctuation (.,) added as 'orphans' to keep at end of line
- PNG files - was still buggy reading larger PNG files (due to fread)

Files updated:

mpdf.php
htmltoolkit.php
CJKdata.php
/patterns/.. (new files)

Developers only

Variables renamed as more accurate or appropriate:

- var \$isunicode renamed as \$is_MB
 - var \$usingembeddedfonts renamed as \$usingCoreFont
- CJK changed to act internally as UTF-8 encoded
- (NB CJK Half-widths not supported from 2.5+ i.e. big5-hw gb-hw)

=====

mPDF v2.4 (23/04/2009)

=====

Files updated

mpdf.php
htmltoolkit.php
mpdfi/mpdfi.php

New files

graph.php

Graphs - Requires new folder: path_to_mpdf/graph_cache/ (must be writeable)

New features

Annotations improved so they appear as a pop-up

Re-use Document Templates (cf. RestartDocTemplate() in manual)

Limited support for CSS float property on an IMG element allowing text wrapping e.g. (cf. Images in manual)

Utility function PreparePreText() allows output of a text file which may include <pre>

Automatic generation of graphs from data in tables (requires integration with JGraph) (cf. Graphs in manual)

Other Changes

IMPORTANT - User rights removed as not working with newer version of Adobe Reader 9 (affects Active forms and ability for users to modify annotations)

Corrects text alignment when using {nb} or {nbp} in (non-HTML) headers/footers

Sets default timezone if not already set (at top of mpdf.php) to prevent E_STRICT ERROR message

Suppresses E_NOTICE error reporting (at top of mpdf.php)

Error capture in Output() to avoid PDF header being sent when error messages generated

A function str_replace added to htmltoolkit to allow PHP4 to function

Bug fixes

WMF images incorrectly positioned when in-line

PNG images > 8kB failed to load - (fix in 2.3 didn't work - fixed properly this time)

Annotations containing a new line (\n) causing an error

Evaluation of <pre> text: "<code>[TAB] " evaluated incorrect number of spaces to follow to align tabs, because < was calculated as 4 chars (<)

=====

mPDF v2.3 (22/03/2009)

=====

New Features

- Optionally detect language and when to use special fonts i.e. RTL (arabic), CJK (chinese), Thai (see SetAutoFont() etc.)

- Supports HTML attribute "lang" in all tags and uses special fonts when required (see \$useLang)

- Joins Arabic and Farsi/Persian text into presentation forms

- Import another PDF file and use as templates in your document (see UseTemplate() and mPDFI in the manual.)

- Replace specified text strings in an existing PDF file (see OverWrite() etc.)

- More than one Table of Contents can be used in a document (see tocpagebreak etc.)

- Restore properties of open HTML block elements after a page break (variable \$restoreBlockPagebreaks or new tag <formfeed>)

- <annotation> <bookmark> <indexentry> <tocentry> can now accept characters <>'& as htmlentities - htmlspecialchars(..., ENT_QUOTES)

- <annotation> can now accept "\n" for new line

- support for opacity (CSS3 property) for images

- specify the number of spaces to substitute for TAB when parsing <pre> tags

- greater control over margins and display when changing page orientation during document (see \$forcePortraitMargins and \$displayDefaultOrientation)

Bug fixes

Fonts in CSS - Not parsing font-family: Trebuchet MS; correctly as trebuchet

Fonts in CSS - CSS font-family: [unknown]; setting first \$available_unifont rather than ignoring

Images - not displaying on IIS platform

Images - .wmf not displaying if (allow_url_fopen) not set
Table borders - in defaultCSS, 'MARGIN-COLLAPSE'=> collapse not quoted therefore not working
Line-break inside table - printing a blank background across page rather than just going down a line
Form fields inside tables - will now resize if the table is autosized (shrunk)
<pre> containing a '<' was changed to '<'
Tabs inside <pre> were all changed to 8 spaces, not the remainder following a string
Header on first page was inset by 1mm left and right (\$cMarginL and \$cMarginR not set to zero)
Table nested inside a cell with colspan > 1 was incorrectly handled
PNG file crashed (?incorrectly defined PNG file) [adapted _parsepng to account for unexpected]
Table or Cell - if font-size not recognised, mPDF set font-size to zero
Font-sizes - [xx-small|x-small|small|medium|large|x-large|xx-large] were not recognised in tables

=====
mPDF v2.2.1 (17/02/2009)
=====

Bug fix - (bug introduced in 2.2)
Table - header row did not return to top of page when repeating across pages.

=====
mPDF v2.2 (15/02/2009)
=====

Updated files from mPDF 2.1
mpdf.php
htmltoolkit.php
mpdf.css (new)
=====

New files from mPDF <2.0 (only required for EAN Barcodes)
font/ocrb.xx (several)
unifont/ocrb.xx (several)
IMPORTANT - you need to make sure the ocrb font is added to the config.php file
- add 'ocrb' to the end of 3 arrays: \$this->available_fonts \$this->available_unifonts and
\$this->mono_fonts
=====

Summary of changes

- external stylesheet file (mpdf.css) is used to configure default values (\$useDefaultCSS2 and \$defaultCSS2 are no longer used)
- special comment tags to hide mPDF tags from browsers: <!--mpdf ... mpdf-->
- AddColumn() function added (equivalent to <columnbreak>)
- annotations - pop-up messages the reader can move or delete (if you set permissions)
- support for WMF images as well as GIF, JPG, PNG
- watermark image can be set instead of, or as well as text
- nested tables can include other content
- improved control over table layout
- margin: auto now supported for table and block elements

A number of methods and variables have been renamed or reCapitalised for consistency.

Changes should be backwards compatible.

All user methods start with a Capital, all user-defined variables start with lowercase.

Affected:

Reference() -> IndexEntry()
CreateReference() -> CreateIndex()
\$TopicIsUnvalidated -> \$showWatermark
setUnvalidatedText() -> SetWatermarkText()

PHP appears at present to be case-insensitive for function/method names

All the following functions have been renamed in the script with a capital first letter:

setUserRights()
setBasePath()
setAnchor2Bookmark()
setHeader()
setFooter()
defHeaderByName()
defFooterByName()
setHeaderByName()
setFooterByName()
setHTMLHeader()
setHTMLFooter()

```
defHTMLHeaderByName()  
defHTMLFooterByName()  
setHTMLHeaderByName()  
setHTMLFooterByName()  
shaded_box()  
writeBarcode()
```

Variable names changed to lowercase first letter:
(Variables are case-sensitive therefore aliases have been set up)

Anchor2Bookmark
BiDirectional
KeepColumns
AliasNbPg
AliasNbPgGp

=====
Bug fixes
=====

Columns - \$keepColumns=true was incorrectly calculating the place to continue printing after 1 and half columns (of 3)
Table cell height - incorrectly setting table cell height when cell contained a line of text of large size which wrapped to more than one line
HR in Table cell - if table cell contains only HR (and column otherwise empty), HR was printed outside cell
HR in Table cell - if table cell ended with a HR, height was one line too much
Table page-break-inside:avoid - caused mPDF into permanent loop in some circumstances
Paging - Total Pages/Group {nb} and {nbgp} didn't work in CJK
CSS - Border size thin, medium and thick were only recognised in lowercase
Table-header - rowspan not correctly output in THEAD
Default CSS - table empty-cell:hide changed to show (CSS specification)

=====
mPDF v2.1 (24/01/2009)
=====

New Features in Version 2.1

-
- CSS support improved generally (especially for cascading CSS, lists)
 - TableHeader changed to allow multiple rows in THEAD

CSS changes

-
- display: none (block elements only - not lists or tables, nor HR)
 - width (TD/TH)
 - list-style-type (will also recognise the list-style-type from list-style) (OL/UL)
 - recognised values: disc|circle|square|decimal|lower-roman|upper-roman|lower-latin|upper-latin|lower-alpha|upper-alpha|none
 - CSS support for : font-family, font-size, font-style, font-weight, color, background-color, text-decoration, text-transform, and list-style-type (will also recognise the list-style-type from list-style)
 - table cell borders - CSS rules have been adapted slightly - if a coloured/black line conflicts with a white line, and is the same width, coloured/black will overwrite even if Bottom or Right

Numbered Lists

-
- Variables set at the top of mpdf.php can be set to change:
- text alignment of numbers in numbered lists (default Right)
 - var \$list_align_style = 'R';
 - content to follow a numbered list marker e.g. '.' gives 1. or IV. whereas ')' gives 1) or a)
 - var \$list_number_suffix = '.';
- (These can be altered at run time, but are not changeable through stylesheets or in-line style)

Writing broken segments of HTML

2 new parameters have been added to WriteHTML()
function WriteHTML(\$html,\$sub=0,\$init=true,\$close=true) {
\$close - Leaves buffers/variables etc. in current state, so that it can continue to write the HTML

where it leaves off

\$init - Clears and resets buffers/variables

(N.B. You must end with a WriteHTML that calls \$close=true)

Example:

```
$mpdf->WriteHTML('<p>This is the beginning...', 2, true, false);
```

```
$mpdf->WriteHTML('...this is the middle...', 2, false, false);
```

```
$mpdf->WriteHTML('...and this is the end</p>', 2, false, true);
```

Rotated text in table cells

NB This UPDATE will change expected output from previous versions*****

Prior to v2.1 any cell set to rotate text anticlockwise was forced to vertical align = bottom.

This has been changed so that it only overrides when the rotate angle is between 45 and 89 degrees:

text rotated exactly 90 degrees will respect the set value for vertical-align.

=====

Bug fixes

=====

- List - list starting after "<div>Then some text not in a block element" incorrectly output
- Tables - if cell font-size set smaller than default for the table, does not shrink the cell height
- Columns (tables) - columns breaking across rows e.g. in the middle of a table cell
- Tables - if table width set to e.g. 100% but cols are less, was not making up to set width
- Watermark - was not printing if using HTMLFooter
- Lists - not aligning numbering correctly if different font sizes used for bullet & text etc.
- Lists - indent of text did not correctly allow for Maximum number in list
- Table does not always move correctly to a new page
- Table cell incorrectly calculated height causing text to overflow cell when printed
- Table borders in columns not being correctly handled (bug since 2.0 introduced a buffer to save the borders and print at the end of the table - fixed so does not use buffer if in columns - potentially does not deal with conflicting borders as well, but works in columns)
- Table cell width if set as a percent was being downsized when autosizing table
- Table CSS was buggy - improved
- SetBasePath (when fetching remote website) - now handles string with query string on it e.g. <http://www.domain.com/index.php?tid=42>
- Table cells with Rotated text - text not positioned correctly
- Page number totals not working in utf-8 mode

=====

Code efficiency improvements

=====

- BIG speed improvement (compared with 2.0) with tables (especially large tables)
- considerable increase in speed if writing long HTML segments to mPDF
- speed improvement for tables (may be very significant if some cells have a lot of text in them causing uneven column widths)

NB To speed up program more, consider setting \$mpdf->useSubstitutions=false; if you do not use any characters outside the codepage selected

=====

Keep-with-table

=====

(This was introduced in v2.0 but I forgot to document it)

If you set \$this->use_kwt = true;

All H1-H6 elements will try to keep with a table that follows immediately afterwards - (this is done in htmltoolkit, by adding an attribute KEEP-WITH-TABLE)

See Known Issues re: Using kwf inside a div with border/background (doesn't work)

=====

mPDF v2.0 (07/12/2008)

=====

Main New Features in Version 2.0

- nested tables are supported

- supports both models of table border: separate and collapsed
- improved parsing of CSS stylesheets, and better handling of styles throughout
- additional recognised CSS styles
- page orientation, size, and margins can be changed within the document, using PHP script or custom HTML
- some limited support for @page CSS to define page-box areas, with crop/cross marks for printing
- improved control over headers and footers (including HTML headers/footers)
- improved presentation of Form elements including image-type input fields
- generates an EAN barcode suitable for a book/printed publication
- active forms can be generated - EXPERIMENTAL at present
- change document permissions to allow the user to make annotations - EXPERIMENTAL at present

NB Lines are commented in mPDF script as changes for mPDF 1.4 - this became v2.0

=====
UPGRADING
=====

IMPORTANT - Before Upgrading: Please note that some of the changes will cause mPDF 2.0 to render the pages differently from earlier versions i.e. it is not totally backwards compatible. Read the notes on Backward compatibility before deleting your original set-up.

To upgrade from v<=1.3 to v2.0 you only need to copy and overwrite the following 2 files:

mpdf.php
htmltoolkit.php

Plus (optionally) if you want to use the EAN Barcode function, you will also need:

font/ocrb.xx (several)
unifont/ocrb.xx (several)

IMPORTANT - you need to make sure the ocrb font is added to the config.php file
- add 'ocrb' to the end of 3 arrays: \$this->available_fonts \$this->available_unifonts and \$this->mono_fonts

=====
Bug Fixes
=====

<columns column-count="0"> did not turn off columns - Fixed

Margins as % - e.g. margin-right: 50% set from CSS incorrectly applied 50% of the fontsize
(Fixed - adding parameter to fn.ConvertSize in htmltoolkit.php and in calls to that function)

DIV Width - e.g. div style="width: 50% was not working
(Fixed - fn.SetCSS and OpenTag()'DIV')

CSS values as Zero - p { margin: 0; } did not work in stylesheet unless 0 had a unit

Multiple Non-breaking spaces collapsed - e.g. "1 2" - was contracted to "1 2"
(Fixed - fn.adjustHTML in htmltoolkit.php)

Table cell too narrow causing incorrect printing - If two characters are too wide to print (only likely within a table cf. example tables - Periodic table) the first character was not printed, just a new line
(Fixed in fn.WriteFlowingBlock)

Font size by inline style for form elements <input> <textarea> gave wrong size when using a relative size 0.9em
(Fixed - fn.ConvertSize in htmltoolkit.php)

Creation Date not correctly showing
(Fixed - did not need to convert to UTF16)

New block element started at end of page - block borders not painted
(Fixed - fn.AddPage)

DL did not close block correctly
(Fixed - mistype in fn.CloseTag)

Transparent not recognised as color/background-color
(Attempted a fix by setting to ignore it! - fn.convertcolor in htmltoolkit.php)

Zero (0) not displaying if only thing in table cell or tags e.g. `<td>0</td>` `<p>0</p>`
(Fixed - `fn.WriteHTML`)

Page Headers/Footers - Simple Headers or Footers defined as e.g. `'|{PAGENO}|'` were not split into 3 components, but output `|6|` in the outer margin.
(Fixed)

Could not copy from a completed PDF doc to clipboard when using a TrueTypeUnicode font
(Fixed - `fn._puttruetypeunicode` - added `CIDToGIDMap`)

Creating an Index (confusing called `CreateReference` in mPDF) based on only 1 column (i.e. columns off) caused it to print FAIL
(Fixed - `fn.CreateReference()`)

Table of Contents - If a ToC entry reached other side of page a warning notice was produced
Fixed - printing is now suppressed and it is moved down a line (but not when using `rtl`)

"Keep Block Together" (i.e. `page-break-inside: avoid` for a block element)
If this property causes some text to be moved to the next page, internal link targets (i.e. ``) were incremented `pagenumber` by +1 - as this used the calculated document page number, didn't work if using e.g. roman numerals
(Fixed)

NB This is now ALWAYS disabled when it meets a table - can use `page-break-inside:avoid` for the table

`@import url(style.css)` without quotation marks `""` was not picked up, although it is valid HTML
(Fixed - `fn.ReadCSS()`)

Reading CSS from external style sheets included all media
Now set by default to ignore `media="aural|braille"`
Allows `media="print"` but can exclude by: `$mpdf->disablePrintCSS = true;` (default = false)
Works on both `<link...` and `<style media="print">@import...`
See the web page example - this stops the CSS stylesheets specifically marked for "print" to be ignored

Table borders (in collapsed model) incorrectly calculated which border had dominance (mPDF <=1.3 determined the overriding border by its color)
(Fixed to follow CSS 2.1 specifications: `width >> CSS dominance (cell>table) >> T & L > B & R`)
In the border-collapse=collapse mode, the following rules determine which border style "wins" in case of a conflict:

1. Borders with the 'border-style' of 'hidden' take precedence over all other conflicting borders.
2. narrow borders are discarded in favor of wider ones.
3. styles are preferred in this order: 'double', 'solid', 'dashed', 'dotted', 'ridge', 'outset', 'groove', and the lowest: 'inset'.
4. If border styles differ only in color, then a style set on a cell wins over one on a table.
5. When two elements of the same type conflict, then the one further to the left or top wins out.

Parsing CSS, a missed level would not be picked up i.e. `CSS = div.refstr1 p {...}` would not pick up:
`<div class="refstr1"> <div class="another"> <p>...`

(Fixed - `fn.MergeCSS` by carrying everything forwards)

Note: I removed - `&&`

`!$this->blk[$this->blklvl-1]['cascadeCSS']['CLASS>>'].$attr['CLASS']]['depth']`

Not sure why I put it there in the first place!

In a later bit of function - `&& $this->blk[$this->blklvl-1]['cascadeCSS'][$tag]['depth']>1`

Haven't removed this, but is it needed???

CSS inline style set in TD/TH (font-size, color, weight, font-family or italic) didn't turn off at the end of the cell (and also formatted the top left cell)
(Fixed)

CSS properties color, font-weight, and font-style set on a table were not inherited by the table cells
(Fixed - `var $base_table_properties`)

When rotating a table, the text following was positioned incorrectly
(Fixed - `fn.printtablebuffer`)

When rotating a table, links were not adjusted in position e.g. `...`
(Fixed - `fn.printtablebuffer`)

If a larger border-thickness was set for a cell in the middle of a table, cells before that inaccurately calculated the cell width needed

(Fixed)

Text in a table cell which was not in a block and followed a list, there was no line break e.g.
Text following</td>

(Fixed - var \$listjustfinished;)

Setting the default font-family from the body tag using in-line CSS did not work e.g. <body style="font-family:mono"> (did work in external stylesheets)

(Fixed - fn.WriteHTML)

<link href="..." rel="stylesheet"> was not recognised (because the href comes before the rel)

(Fixed)

Read linked CSS stylesheet OR @import stylesheet - now includes both.

<tag class="class1 class2"> did not set either class1 or class2. Fixed so that it will now pick out class1 (better than nothing!)

CSS line-height as % - interpreted 120% as 120 (x the font-size) - Fixed so it now accepts % and numbers

Setting the basepath (used for relative links/external stylesheets etc) with \$mpdf->setBasePath() was generally buggy!

Now allows a domain e.g. \$mpdf->setBasePath("http://www.domain.com"); (previously needed slash on end)

(Fixed - hopefully!)

If you were repeatedly calling mPDF in a loop to produce more than one PDF file, it would crash with error: "You have restricted the number of available fonts to 0". Fixed by editing line 751

require(_MPDF_PATH.'mpdf_config.php'); to require(...

=====

Improvements(?)

=====

Unsupported image files - mPDF died with an error message if image files didn't meet expected format e.g. an interlaced PNG file

Changed so images are now replaced by the NOIMG image.

Footer margin (HTML and normal footers) now determines the lowest point that is printed (rather than the place to start printing the footer)

NB IMPORTANT CHANGE - not backwards compatible

Tabs in <pre> or <textarea> are now replaced by 8 spaces rather than 6 (consistent with <http://www.w3.org/TR/1998/REC-html40-19980424/struct/text.html#edef-PRE>) [fn. AdjustHTML() in htmltoolkit.php]

To insert the total number of pages in the document anywhere in the doc, just use '{nb}'

The line: \$mpdf->AliasNbPages();

has now been uncommented allowing {nb} to be used

NB This will always give the total no. of pages in the whole document regardless of any changes you have made to page numbering.

You can change the default placeholder '{nb}' to any string using: \$mpdf->AliasNbPages(['**my Chars**']);

\$mpdf->AliasNbPageGroups(); default="{nbpg}"

Can be used to set the total number of pages in the current group i.e. between where page numbering is reset

CSS border correctly fixes "solid 3mm #000000" i.e. (style width color) - (not a bug, but this is often incorrectly specified)

Can now print div background behind a rotated table.

You can keep columns as they are i.e. 1st column will finish page then start on second, by setting \$mpdf->KeepColumns = true;

Image constrain

=====

Image size is constrained to current margins and page position. Extra parameter added to end of fn. allows you to override this.

```
$mpdf->Image('files/images/frontcover.jpg',0,0,210,297,'jpg','',true, false);    // e.g. the last
"false" allows a full page picture
Useful for e.g. a cover page for your document
```

Cumulative CSS

=====

In version <=1.3, if you call:

```
$mpdf->WriteHTML($stylesheet,1);
```

```
$mpdf->WriteHTML($html);    // this one cleared the array $this->cascadeCSS; conatining cascaded CSS
information from stylesheets
```

You were meant to call:

```
$mpdf->WriteHTML($html,2); // which doesn't re-parse the CSS information
```

v2.0 changed so that

```
$mpdf->WriteHTML($html); no longers clears the array $this->cascadeCSS and so can be used repeatedly;
```

Additional CSSstyles & HTML attributes supported

=====

<BODY> - font-style, font-weight, color

 - html attributes width="" and height=""

<TABLE|TD|TH> - border: 'thin' 'medium' and 'thick' are now converted to 1px, 3px and 5px

<TABLE|TD|TH> - border now respects all types - e.g. 'double', 'solid', 'dashed', 'dotted', 'ridge', 'outset', 'groove', and 'inset'

(NB mPDF only supports a full declaration of border e.g. "border: thin double #000000;")

<TD|TH> - CSS style="white-space: nowrap" and HTML attribute nowrap="nowrap"

<TABLE> - page-break-inside: avoid

<TABLE> - border-collapse: separate|collapse

<TABLE> - border-spacing: 2px 2px; (horizontal/vertical) or just one figure (both) NB same as cellSpacing

<TABLE> - empty-cells: hide|show (border-collapse:separate only)

<TABLE> - margin-left and margin-right (previously only supported top and bottom)

<TABLE> - padding: (this was incorrectly used for TD/TH before) (border-collapse:separate only)

<TD|TH> - padding:

<TABLE|TD|TH> - inline style "background" works (with a color only) the same as "background-color"

NB Table page-break-inside, autosize values and rotate are only respected for that set on first level table of nested tables

<TABLE> - cellSpacing and cellPadding HTML attributes:

NB cellSpacing is the same as CSS style "border-spacing"

NB cellPadding is a <table> attribute, but sets the cell padding - not table padding

<TABLE> - align="..." now works with a rotated table - but sets the alignment ignoring the rotation i.e. align=right sets the table to the right side of the page (looking as though it is bottom-aligned)

<BLOCK ELEMENTS> - page-break-before: always|left|right - NB any surrounding block tags will be closed before the new page is inserted.

@page - see notes on Paged Media

Unsupported HTML attribute

=====

<TD border="1"> - not valid HTML - no longer supported

Additions

=====

"Keep-with-table"

```
$mpdf->use_kwt = true;    // default=false
```

If set to true, will force any H1-H6 header immediately preceding a table to be kept together with the table

- automatically sets the table to fit on one page (i.e. page-break-inside=avoid) if it is a rotated table

- ignored if: Columns on, Keep-block-together active (page-break-inside=avoid for surrounding BLOCK), active Forms

=====
Notes
=====

NB Not a change - but note you can use this to allow you to feed html code encoded in other than utf-8:

```
$mpdf->allow_charset_conversion=true;  
$mpdf->charset_in='windows-1252';      (needs suitable codes for iconv i.e. windows-1252 not win-1252)
```

Fixing Optional tags

=====

php.net website has illegal nesting of <dt>.. <dd> .. </dd> .. </dt> and <p>.. <div> .. </div> .. </p>

The example which parses the php.net webpage will not show correctly unless you change:

```
$mpdf->allow_html_optional_endtags=false;
```

Trying to fix incorrect (X)HTML with \$mpdf->allow_html_optional_endtags==true cancels the P when it meets a DIV etc.

EAN barcode

=====

An EAN barcode can be generated

```
function writeBarcode($code, $showisbn=1, $x='', $y='', $size=1, $border=0, $paddingL=1, $paddingR=1,  
$paddingT=2, $paddingB=2) {
```

It accepts 12 or 13 digits with or without - hyphens as \$code e.g.

```
$mpdf->writeBarcode('978-1234-567-890', 1, $mpdf->x, $mpdf->y);
```

NB - IMPORTANT***

A new font - OCR-B font/unifont is required, and needs to be added to the config.php file

cf. http://www.gs1uk.org/downloads/bar_code/Bar_coding_getting_it_right.pdf

Barcode size must be between 0.8 and 2.0 (80% to 200%)

CMYK Colors

=====

Functions - SetDrawColor, SetTextColor and SetFillColor all now take an optional 4th parameter.

If defined this will interpret the input as CMYK color i.e.

```
SetDrawColor(15,82,0,10)      // NB all values out of 100 - not 255 as for RGB
```

htmltoolkit.php fn.ConvertColor() - now interprets custom color definition: cmyk(15,82,0,10)

like rgb(r,g,b) except values out of 100

Intended to be used for calling the functions separately - BUT works in a limited way with CSS - does not get reset or inherited correctly

```
<p style="color:cmyk(215,31,15,10)"> does work
```

DEFAULT CSS

=====

\$defaultCSS has been updated to reflect better the standard HTML default e.g. using serif, table borders separate, cell vertical-align top

To keep mPDF 1.3 (my favourites) I have introduced:

```
$mpdf->useDefaultCSS2 = true;
```

=====

Permissions - forms and Annotations - Experimental!

=====

You can set the Permissions for the PDF file to allow the user to make Comments (annotations)

```
$mpdf->setUserRights($enabled=true[default]|false, $annots="/Create/Delete/Modify/Copy/Import/Export",  
$form="/Add/Delete/FillIn/Import/Export/SubmitStandalone/SpawnTemplate",  
$signature="/Modify") )
```

If you encrypt the file, make sure the permissions match e.g.:

```
$mpdf->setUserRights();
```

```
$mpdf->SetProtection(array('print','annots'),'yourPassword','myPassword');
```

To allow this, changed the PDF-file version to %PDF1.5 (NB Probably needs PDF version > 1.5 but can't

test for this...)

NOTE: If you output the PDF file straight to the browser, it will only allow annotations after you save the document

=====

Active Forms - Experimental!

=====

At present , using active forms will prevent any internal and external links - that appear before active forms(?) - from working (why?)

May need to save form for proper use - see example, when scroll forwards and back, the form disappears??

Need to set UserRights (see above), and \$mpdf->useActiveForms=true;

For Output options, see separate notes.

=====

Internal Programming changes

=====

NB fn. tablerotate in htmltoolkit no longer used; now uses a 'transform' to shift the whole block of PDF code

Graphics State

=====

ExtGState does not need to be redefined - e.g. if a watermark added on every page, turning on and off alpha/transparency

Unnecessary file size.

function AddExtGState() edited to check if graphics state already exists before adding new one

ASCII-proof code

=====

Images

=====

- 1) When copying remote images locally - incorrectly used "unset" now changed to "unlink"
- 2) When parsing image files - was using CURL for any image src="http://... - even if this was on the local server - edited so it only uses CURL if necessary/appropriate.

NB Handling images was updated in v1.3 because my ISP changed allow_url_fopen to false

Fixed so mPDF tests if the file is available as a local call e.g. getimage('images/test.jpg') even if it is defined as a full URI e.g. http://www.mydomain.com/images/test.jpg as this is quicker(?), and permitted even if allow_url_fopen is false.

If not available as a local file (and allow_url_fopen is set) mPDF tries to use fopen/file_get_contents using an http wrapper;

Else, if CURL is available and allow_url_fopen is false: then tries using CURL.

(Clear as mud???)

=====

mPDF v1.3 (21/09/2008)

=====

Page Numbering

Program changes:

fn. startPageNums() replaced with blank function

fn. stopPageNums() - deleted

fn. numPageNo() - deleted (all it did was return this->page anyway).

var \$_numbering - deleted

var \$_numberingFooter - deleted

var \$_numPageNum - deleted

NEW

New: fn. AddPages() (as for AddPage but with type=NEXT-ODD or NEXT-EVEN see below)

Edited: fn. AddPage() - new parameters added

AddPage(orientation(NO),type="E|O", resetpagenum="1|0", pagenumstyle="I|i|A|a|1", suppress="on|off")

New: fn. docPageNum() - returns the document page number (or '') based on...

New : PageNumSubstitutions(array)

New attributes:

```

<pagebreak resetpagenum="1" // resets document page numbering to 1 from the new page onwards
<pagebreak suppress="on" // turns on suppression of page numbering i.e. in headers and footers,
{PAGENO} is replaced by blank string
// ="0" turns suppression off
<pagebreak pagenumstyle="I|i|A|a|1" // (re)sets page number style/type from the new page onwards -
as for lists
// 1 - decimal; A/a - alpha (uppercase/lowercase); I/i - Roman
(uppercase/lowercase)
<pagebreak type="NEXT-ODD" // always adds a page + another if required to make odd
<pagebreak type="NEXT-EVEN" // always adds a page + another if required to make even

```

Edited: fn. TOC() // sets the marker for a Table of Contents
 New parameters allow the page-numbering details to be set
 NB the page-numbering details set are for the page which follows on after the TOC marker is inserted.
 The page-numbering for the actual ToC is set later, when the ToC is generated and inserted here
 new parameters as above for pagebreak resetpagenum="1|0", pagenumstyle="I|i|A|a|1", suppress="on|off"

Can also be set by attribute in the <TOC>
 <TOC resetpagenum="1" pagenumstyle="I|i|A|a|1", suppress="on|off" />

 Changes to allow Rotated Text in table Cells

Edited:
 fn. OpenTag()
 fn. _tableColumnWidth()
 fn. _tableHeight()
 fn. _tableWrite()
 fn. tableHeader()

New custom style or attribute -- "text-rotate" -- can be set for either <tr> or <th|td>
 Allowed values: 45 - 90 (written as integers) - rotates text anticlockwise, and -90 (clockwise)
 Positive values less than 90 force cell to: vertical-align:bottom

Limitations:
 Only allows single line of text;
 Font, font-size, and style are determined by those set for the cell, and cannot be changed;
 No changes in font (or any other in-line changes e.g. <sup>) are supported within the text

Example: <tr style="text-rotate:90">...

 Bug fixes

1) HTML footer containing table was triggering page break.
 Added \$this->InHTMLFooter as flag to prevent page triggering in footers containing table
 Set in fn.writeHTMLFooters() -> in fn.tableWrite() stops the pageBreak being reset

2) Crashing when libcurl not installed.
 Edited OpenTag() curl_init - added if (function_exists) to exclude crash when libcurl not installed

3) Single cell with borders not showing the borders.
 e.g. <table><tr><td style="border:1px solid #000000">Hi</td></tr></table>
 Problem: mPDF overrides cell border properties with table border properties for external borders.
 \$defaultCSS had CSS defined for table as '0px solid #000000'
 Quick fix - line 273 removed. A more complete fix will require reprogramming to distinguish between
 "border property not set" and border property set as "none".

4) Empty textarea incorrectly handled (the following HTML code being output in the textarea)
 The html code for an empty textarea was incorrectly handled in htmltoolkit fn. AdjustHTML which has
 been edited

```

=====
mPDF v1.2 (2008-05-01)
=====
// Added v1.2 option to continue if invalid UTF-8 chars - used in function is_utf8()
var $ignore_invalid_utf8 = false;

Reading CSS in fn. ReadCSS() and applying in fn. MergeCSS() -

```


Edited to allow Tags, class and id with the same name to be distinct i.e. h5 {...} .h5 {...}
#h5 {...}
* mPDF 1.2 This version supports: .class {...} / #id { }
* ADDED p {...} h1[-h6] {...} a {...} table {...} thead {...} th {...} td {...} hr {...}
* body {...} sets default font and fontsize
* It supports some cascaded CSS e.g. div.topic table.type1 td
* Does not support non-block level e.g. a#hover { ... }

Table: font-size, weight, style, family and color should all work
TD/TH: font-size, weight, style, family and color should all work

Added to htmltoolkit - fn.array_merge_recursive_unique()

memory_opt Removed in mPDF v1.2 - not working properly

fn. _begindoc() - changed to %PDF1.4 (was 1.3) as PDF version

Write HTML Headers and Footers

fn. Close() - calls writeHTMLHeaders/Footers() before finishing doc
fn. WriteHTML() - added parameter
fn. _out - writes to outputbuffer when writing HTML footers/headers

New

fn. writeHTMLHeaders()
fn. writeHTMLFooters()

=====
mPDF v1.1 (2008-05-01)
=====

Programming changes to increase efficiency

fn. WriteHTML() - added lines to combine substituted characters <tta> etc

Memory Optimization added (script from FPDF site) - edited fn. _putpages() and fn. _endpage()

fn. SetFont() edited to return val quicker if font already set (increase efficiency)

new vars chrs and ords are used to store chr() and ord() - quicker than using functions

fn.setMBencoding() - only call mb_internal_encoding if need to change

Bugs

fn. SetDefaultFontSize() - edited to allow to override that set in defaultCSS

fn. Output() - Added temporary(?) disablement of encryption in CJK as it doesn't work!

fn. OpenTag() [LI] \$this->blockjustfinished=false to prevents newline after first bullet of list within table

Uses of mb_ereg_replace removed, and mb_split changed - requires regex_encoding (regex_encoding only used as UTF-8)

fn. WriteHTML: attributes are trimmed with trim() to allow correct handling of e.g. class="bpmBook "

fn. printbuffer() and fn. openTag() to ensure
<div><div><p> outputs top margins/padding for both 1st and 2nd div
and </p></div></div> ...

fn. SetFont() added line - bug fixing in CJK fonts

CSS functionality

Added special CSS 'thead-underline' (similar to topntail)

var \$thead_font_weight; added (openTag) to enable setting of font-weight for <TH> cells

Fixed table border inheritance: Table border inherits border="1" to cells, but not table style="border..."

"page-break-inside: avoid" added (var keep_block_together) to allow a DIV or P to be kept on one page

- not compatible with table autosize or table rotate
- only works over maximum of 2 pages

Enhancements

Orphans in line justification: R. Bracket) added to defined list of orphans

allow_url_open

Following a change in the PHP ini config set on my website by my ISP, changes made to allow mPDF to work with allow_url_open=OFF.

- file_get_contents() changed to use libcurl (for CSS files)
- openTag('IMG') @fopen() and 3 functions _parsegif, _parseJPG, _parsePNG, edited to copy remote image files to local file to include images

FlowChart

Changes to enable mPDF work with a custom script producing Flowcharts:

- WriteHTML() second parameter=3 will allow HTML to be parsed but not output
- fn. Arrow() added
- TableWordWrap() added parameter to force array return